



This compact, minimalist printer offers a splash-proof cubic design, a convenient front receipt printout –and a low power motherboard, together with a triple interface.

Specially designed for point of sale and service applications, the **ODP 333** by **AURES** is a thermal receipt printer which features a triple interface (including Ethernet) in a minimalist compact and cubic style, available in black or white.

With its front receipt printout, it ensures optimum protection against dust, crumbs and liquid splashes in tough environments such as kitchens, restaurants, bars, bakeries and the like.

Thanks to its *Energy Star** certification, it switches automatically to stand-by mode in less than one second after it stops printing, allowing average power savings of at least 30% - embodying and thus respecting the values of Green IT.



ODP 333

- Contemporary black or white cubic design
- Highly compact ergonomic format
- Low power motherboard
- Integrated Triple interface (Serial RS 232C Serial, USB, & Ethernet)
- Splash-proof receipt printout path located on the front side for enhanced protection; perfectly designed for all catering and hospitality sectors.
- Print speed: 160mm/sec
- Configuration utilities
- All cables supplied



| MODEL | ODP 333 |
|-----------------------|---|
| Print method | direct, thermal |
| Print speed | 160mm/sec |
| Effective Print Width | 72mm / 512 dots/line |
| Characters per line | Font A: 42 columns, 180dpi Font B : 56 columns, 180dpi / 64 columns, 203dpi |
| Internal memory | 64MB |
| Motherboard | low power consumption – automatic standby mode enables 30% less power use on average. |
| Paper loading | automatic |

T H E R M A L P R I N T E R

| | |
|--------------------|--------------------|
| Width: | 79.5 mm +/- 0.5 mm |
| Thickness | 0.065 - 0.1mm |
| Max. roll diameter | 83mm |

C H A R A C T E R S

| | |
|--------------------------|---|
| Alphanumeric | 95 |
| Extended graphic | 128 x 18 page |
| International characters | 14 |
| Barcodes | UPC - A, UPC-E, EAN-8, Code 39, Code 93, Code 128, ITF, Codabar, 2D PDF417, QR Code |
| Emulation | ESC/POS compatible |
| Drivers | Windows (XP, 2000, 2003, Vista, WEPOS) /OPOS / Linux / Java POS |
| Sensor | end-of-roll, near end-of-roll, cover open |
| Till output port(s) | 1 dual port (for 2 drawers) - RJ11 6-pin connector |
| Interfaces | Triple interface RS232 Serial - USB & Ethernet dual (non-modifiable) |
| Power supply | External 24V - 2.5A |

P A P E R C U T T E R

| | |
|-------------|--|
| Auto cutter | guillotine type Max. 30 cuts/minute |
| Cut type | total or partial |

O T H E R F E A T U R E S

| | |
|-------------------------------------|---|
| MCBF | 35-50 million lines depending on type of use and paper thickness Printer head lifespan: 160km Paper cutter lifespan: Approx. 1.5 million cuts |
| Operating temperature | -20 to +60°C |
| Operating humidity | 10% to 90% (without condensation) |
| Dimensions (depth x width x height) | 165 x 135 x 105.02mm |
| Weight | 1kg approximately |
| Colour | Black or white |

