

TRP 100 III

thermal receipt printer



Low-power
thermal receipt printer

The **TRP 100 III** from AURES features a **low-power motherboard** (Energy Star certified); It switches automatically to standby mode less than a second after it stops working, *ensuring average power savings of at least 30%* – and thus *embodying the values and requirements of Green Technologies.*

The **TRP 100 III** can hold paper rolls up to 80mm in diameter. It features an ESC/POS compatible driver and easy paper drop in, delivering high printout quality.

The printer is available with a native **USB type B** port and a removable **DB25 serial interface**. **Wifi, Ethernet** and **parallel** ports are also available as optional extras.

The **TRP 100 III** offers excellent value for money and caters for a wide range of POS applications.

*(www.eu-energystar.org/fr/index.html)



TRP 100 III

- **Low-power** motherboard
(automatic standby mode enables 30% less power use on average)
- **Energy Star** certified
- Easy paper drop in
- Thermal roll diameter: 80mm
- 200 mm/sec
- ESC/POS compatible
- 2D barcode supported
- Native USB (type B) port + removable serial port
- Optional Ethernet 10/100 T, parallel and WIFI (802.11b) interfaces
- Ready to use: all cables supplied, as well as power supply.
- Easier configuration via utility software
- Available in black or beige



MODEL	TRP 100 III
Printing method	Direct thermal
Printing speed	200 mm/sec
Printing width	max 72 mm / 512 dots
Resolution:	180 dpi x 180 dpi
Characters/line	Font A (12x24): 42 columns Font B (9x24): 56 columns
Paper loading	Easy paper drop in
Motherboard	Low-power Automatic standby mode (uses 30% less power)

P A P I E R T H E R M A L

Width:	50mm-82.5mm
Thickness	0.06-0.09mm
Max. roll diameter	83mm

C H A R A C T E R S

Alphanumeric characters	95
Extended graphics	128 x 18 page (1 space/page)
International characters	14
Barcodes	UPC-A, UPC-E, EAN-8, Code 39, Code 93, Code 128, ITF, Codabar, 2D: PDF 417, QR Code
Emulation	ESC/POS* compatible
Sensors	end of paper, paper low sensor, cover open sensor
Drawer port	1 double port (for 2 cash drawers)
Interfaces	Native USB (type B) + removable DB25 serial port
Interfaces (optional)	Parallel, Ethernet and WIFI
Drivers	Windows Driver (7, XP, 2000, 2003, Vista, XP Embedded), Linux, OPOS, WEPOS, Java POS

P A P E R C U T T E R

Auto cutter	MTBF 1.5 million – guillotine type
Cutting method	Total or partial cut

V A R I O U S

Power supply	External 24V - supplied
Dimensions (LxDxH)	152 x 202 x 150 mm
Weight (including paper cutter)	1.7kg
Colours	black or beige

*ESC/POS is a registered trademark of SEIKO EPSON CORP.

