



This 'all-in-one' touchscreen system is fanless and features a slimline design as well as a splash-proof front. Easy to install anywhere and ideal for wall-mounted till operations, it can also be mounted on a pole (or placed on a stand).

**W-Touch** is an integrated 15-inch touchscreen system that is just 48mm thick. Designed particularly for wall-mounted till applications, it can also be supplied on its stand or pole.

The system is fanless, dust-resistant and splash-proof, offering protection against water and other liquids. The front face complies with **IP65** standards, so the system is ideal for use in harsh environments. **W-Touch** is powered by an

**INTEL Pineview Dual Core D525 processor**, ensuring optimum energy use.

Mounting the system on a wall or a pole saves a considerable amount of space, so **W-Touch** is perfect for all types of sales and service outlets where space is at a premium. It's ideal for retail, takeaway sales, catering and kitchen environments, fast food outlets and mini-markets, as well as food and non-food self-serve stores.

The system can also be easily integrated and adapted to both checkout and self-checkout terminal furniture.

**W-Touch** is available in two colours: graphite black and pure white.

# W-TOUCH

- +
- +
- +
- +
- +
- +

## COLORS

white black



## MODEL

## W-TOUCH

Processor	INTEL Pineview Dual Core D525
Chipset	CPU with Graphic built-in + ICH 8M
RAM	SO DIMM DDR3 2GB expandable to 4GB (2 slots)
Graphics memory	Up to 256 MB shared RAM
Hard drive	SATA 2.5" 320GB hard drive on removable rack
Flash Memory	optional SSD SATA flash drive
Touch screen	Turbo Touch 15" Resistive
Brightness	250cd/sqm (250nits)
Resolution	1024 x 768

## INPUTS / OUTPUTS

Serial/COM	4 ports (2 self-powered)
USB 2.0	4 USB 2.0 ports
Parallel port	1 Sub-D 25 pin connector
LAN 10/100/1000	1 x RJ45
Cash drawer output	1 x RJ11 (12V/24V)
Mike input	1
Audio output	1
Additional video output	1 VGA
Mini PCIe slot (internal)	1

## VARIOUS

Power supply	external, 90W, 19V, 4.7A
Operating temperature	5°C to 35°C (41° F to 95° F)
Storage temperature	20° to 55° C (-4° F to 140° F)
IP 65 standard	Dust and splash-proof front face
Humidity rating (in operation)	20% to 80% (RH without condensation)
Humidity rating (in storage)	20% to 85% (RH without condensation)
Dimensions (W x H x D)	362 x 280 x 48 mm (excluding wall bracket)
Fixings VESA	100 x 100 mm – may be used on a wall-mounted bracket or on a pedestal or stalk.
Weight	7kg
Compatible operating systems	Windows XP Pro, POS Ready 2009, Windows 7 Pro, POS Ready 7, Linux
SSD	1 (optional)
Colours	black and pure white



Specifications are subject to change without notice- © AURES 2014

[www.ares.com](http://www.ares.com)

MANUFACTURER OF REMARKABLY DIFFERENT EPOS TERMINALS

**AURES**