

# ECONOMIC



## 4 inch Barcode Label Printer SRP-770II



### All-in-one



BIXOLON SRP-770II is the first label printer developed with the technological power of Samsung, which has been proved in the POS printer market. The SRP-770II can print 5 ips (127 mm/sec) and can recognize various programming languages such as SLCS, BPL-Z™, BPL-E™ automatically, and also the width of the paper can be adjusted easily to the range of 1.5~4.2 inch so that it can be used for barcode printing as well as receipt printing. The various on-board interfaces including Serial, Parallel, and USB allow flexible system configuration.

BR-SRP-770II-EN-MAR14

Copyright © BIXOLON Co., Ltd. All rights reserved.

Features and specifications are subject to change without prior notice.

### PRINT CHARACTERISTICS

**Print Method** : Direct Thermal

**Print Speed** : Up to 5 ips (127 mm/s)

**Print Resolution** : 203 dpi

**Print Width** : Up to 104 mm

**Print Length** : 6 ~ 304 mm

**Media Sensor** : Transmissive, Reflective, Head open

### MEDIA CHARACTERISTICS

**Media Type** : Gap, Black Mark, Notch, Continuous, Fan-Fold

**Media Width** : 42 ~ 106 mm

**Media Roll Diameter** : Up to 130 mm

**Media Roll Diameter** : 0.06 ~ 0.20 mm

**Supply Method** : Easy Paper Loading

### PHYSICAL CHARACTERISTICS

**Dimensions (W x L x H)** : 184 x 221 x 171 mm  
(7.24 x 8.70 x 6.73 inch)

**Weight** : 1.65 kg (3.63 lbs.)

**Power** : External Power Adaptor 100-240V AC, 50/60Hz

### PERFORMANCE CHARACTERISTICS

**Memory** : 512KB SDRAM, 2MB FlashROM

**Interface** : Triple Interface

Standard: USB V1.1 FS + Serial + Parallel

Optional: USB V1.1 FS + Parallel + Ethernet

### ENVIRONMENT CHARACTERISTICS

**Temperature** : Operating: 0 ~ 40°C (32 ~ 104°F)

Storage: -20 ~ 60°C (-4 ~ 140°F)

**Humidity** : Operating: 10 ~ 80% RH

Storage: 10 ~ 90% RH

### SOFTWARE

**Emulation** : SLCS, BPL-Z™, BPL-E™

**Driver** : Windows Driver, Linux CUPS Driver, Mac Driver,  
Virtual COM USB/Ethernet Driver, Utility Program, Label Artist™

**SDK** : Android SDK

### FONTS / GRAPHICS / SYMBOLOGIES

**Fonts** : • 10 SLCS Resident Bitmap Fonts

• One SLCS Resident Scalable Font

• 23 Code Page

**Graphics** : Supporting user-defined fonts, graphics, formats, and logos

**Barcode Symbologies** : 1D: Coda Bar, Code39, Code93, EAN-8, EAN-13,  
Interleaved 2-of-5, ITF, UCC/EAN-128,  
UPC-A, UPC-E

2D: Data Matrix, MaxiCode, PDF417, QR Code  
(select two only)

### OPTIONS

**Optional** : Ethernet, Auto Cutter

**BIXOLON®**

www.bixolon.com



### BIXOLON Co., Ltd.

7~8F, (Sampyeong-dong), 20, Pangyoyeok-ro241beon-gil,  
Bundang-gu, Seongnam-si, Gyeonggi-do, 463-400, Korea (ROK)

Tel +82 (0) 31 218 5500

Fax +82 (0) 31 218 5589

E-mail sales@bixolon.com

### BIXOLON America Inc.

3171 Fujita St Torrance,  
CA 90505, USA

Tel +1 858 764 4580

Fax +1 310 257 6869

E-mail sales@bixolonusa.com

### BIXOLON Europe GmbH

Tiefenbroicher Weg 35,  
40472 Düsseldorf, Germany

Tel +49 211 68 78 54 0

Fax +49 211 68 78 54 20

E-mail sales@bixolon.de