# **Consumer appealing yet industry proven**

With Multitouch panel – optimized for displaying office documents



- Windows<sup>®</sup> Embedded Handheld 6.5
- **3.7** inch capacitive multitouch display
- IP54 and 1.5m drop resistance
- Pocket size 215g light weight
- Consumer appealing yet industry proven



### **CASIO IT-300**



The IT-300 hand-held business computer is a robust industry PDA that combines simple, intuitive usability with investment protection and the robustness of an industrial hand-held device. The large capacitive colour display can be operated without a stylus and is optimised for displaying PDF documents and office applications. Therefore the IT-300 is, the ideal companion in day-to-day business. It opens up completely new methods of communication and collaboration with the management as well as with all other hierarchy levels - for example in the retail / POS, healthcare and service sectors.



### **Slimline design and intuitive** operation including

Data is either entered via the alphanumeric keypad - in the same way as with a mobile phone – or very conveniently via the large capacitive multi-touch display. Users can zoom in and out and scroll or rotate displayed documents quickly and easily by touching the display with their fingertips. The work without a stylus makes the usage of the device particularly convenient.

### multi-touch display

The 3.7 inch BlanView<sup>®</sup> TFT display with 480x640 pixels offers a crystal clear view in full VGA resolution. It can be read easily in darkness as well as in glaring sunlight and displays extensive PDF documents, EXCEL<sup>®</sup> tables, Powerpoint<sup>®</sup> presentations, graphics and photos, as well as videos (MPEG4/WMV).

Original display size (2.2x3.0 inch)

#### **Robust enough for** tough working conditions

With 1.5-metre drop resistance onto concrete, splash and dust protection in accordance with IP54 and a working temperature between -20° and +50°C, the IT-300 withstands the challenges of the day-to-day work in a number of areas, regardless if it is used indoors or outdoors







#### **Human-centered Design**

The small, light and particularly flat hand-held device fits in the pocket of any shirt or work outfit. Developed in accordance with ISO13407 guidelines of Human-centered Design processes, the terminal fits safely and comfortably in the user's hand thanks to its rounded corners.



## **CASIO IT-300**

### Long battery life and fast operational readiness

The IT-300 is supplied with a powerful lithium-ion battery. Low power consumption was also particularly important. Intelligent power management, the Wireless Standby Mode – where the device is switched off with the exception of the wireless communication functions – and the Quick Start Function from the power-saving mode into operational readiness enable long battery lifes of around 10 hours, as well as fast availability, thereby enabling the user to work more efficiently and provide a better customer service.



#### Versatile software solutions available

TheIT-300 operates on Windows<sup>®</sup> Embedded Handheld 6.5. This means that there is a number of useful applications available to customize the device to the relevant tasks. The Windows<sup>®</sup>- based development environment guarantees investment security and provides the possibility of tailor made applications for specific uses.

#### **Connected at best**

The IT-300 is equipped with Bluetooth<sup>®</sup> 2.0 and WLAN (IEEE802.11b/g) with WAP2 encryption as standard. With a built-in microphone and loudspeaker, the terminal can be used for Voice over IP services.

#### Ready-to-use bundle delivered as standard

For the first time, CASIO is offering the IT-300 as a complete set – with all the accessories required for

immediate use: 1850-mAh battery, USB cable, neck strap, communication and charger adapter.



# **CASIO IT-300**

# www.casio-b2b.com

Specifications		
Model		IT-300-15E
CPU		Marvell® PXA320 624MHz
os		Microsoft® Windows® Embedded Handheld 6.5 English Version
Memory	RAM	256MB
	ROM	256MB (User area: Approx.120MB)
Display	LCD	9.4cm (3.7 inches) VGA (480x640 dots) Blanview® Color LCD with Touch Panel
	Indicator	Indicator 1: Battery charging status Indicator 2: Wireless communication and scanning status
Input	Keyboard	23 keys, numeric (Alphabet) keys, CLR key, execute key, cursor keys, power key, Fn key, F1 to F4 keys, trigger Key
	Touch Panel	Yes (Capacitive type)
Scanner	Туре	Laser
	Resolution	0.127mm
	1D	GS1 DataBar Omnidirectional, GS1 DataBar Truncated, GS1 DataBar Limited, GS1 DataBar Expanded, Code128/GS1-128 (UCC/EAN128), Code93, Code39, EAN8, EAN13, UPC-A, UPC-E, Codabar (NW-7), IATA, ITF, MSI, Industrial 2 of 5, ISBT
	Stacked	GS1 DataBar Stacked, GS1 DataBar Expanded Stacked, GS1 DataBar Stacked Omnidirectional
Wireless LAN	Standard	IEEE 802.11b (Maximum: 11Mbps), IEEE 802.11g (Maximum: 54Mbps)
	Security	WPA2 / AES
Interface	Bluetooth®	Bluetooth® Version 2.0+EDR compatible
	SD-Slot	microSD Memory Card (SDHC)
	USB	Version 1.1 (Host/Client)
	Audio	Microphone: Built-in (monaural), Speaker: Built-in (monaural), Headset Jack 3.5mm
Power	Main Power	Lithium-ion battery pack (Operating period: Approx. 10 hours*)
	Memory Backup	Lithium-ion battery (rechargeable) on board
Durability	Dust/Splash- proof	IP54 (compliant with IEC60529 standard)
	Drop Durability	1.5m
	Operating Temperature	-20°C to 50°C
Vibrator		Comes standard
External Dimensions (WxDxH)		76 × 155 × 19.6mm
Approx. Weight		215g (Including lithium-ion battery pack)

Windows<sup>®</sup> Embedded Handheld 6.5 are registered trademarks of the Microsoft Corporation, USA. The Bluetooth trademark is owned by Bluetooth SIG, USA and licensed to Casio Computer Co. Ltd.. Other product- or company names are either trademarks or registered trademarks of the respective owners. This publication carries product description without obligation and is not to be seen as a firm offer. Specifications and design are subjet to change without notice.



CASIO Europe GmbH · Mobile Industrial Solutions · CASIO-Platz 1 · D-22848 Norderstedt Tel.: +49 (0)40 - 52 86 5-407 · FAx: +49 (0)40 - 52 86 5-424 · E-Mail: solutions@casio.de · www.casio-b2b.com