

# DataMan 50L/60L

#### Small Size

DataMan 50L is just 23.5mm x 27mm x 43.5mm

#### Hotbars Technology

Hotbars provides the highest read rates of 1-D linear barcodes, including those that are damaged, distorted, blurred, scratched, low height or low contrast.

#### No Moving Parts

Designed with **no moving parts** that can become worn out and require replacement.

#### "No Reads" Analysis

The ability to analyze "no reads" by letting the user **see what the reader sees**, either live on a monitor or through image archiving.

The DataMan<sup>®</sup> 50/60L is a new series of compact barcode readers designed for 1-D oriented barcode reading. Small in size but exceptional in barcode reading performance, the **DataMan 50L** measures just 23.5mm x 27mm x 43.5mm and features an IP65-rated housing. It is ideal for mounting in very tight spaces on production lines and in machinery. Both readers are equipped with Hotbars<sup>™</sup>, a proprietary image-analysis technology that delivers the highest read rates in the industry.

#### Models

- DataMan 50L exceptionally small size with USB and RS-232 connectivity
- DataMan 60L offers Ethernet, USB and RS-232 connectivity

#### **No Moving Parts**

Moving parts can wear out and require replacement. The DataMan product line is designed with no moving parts, increasing effective product life and potentially decreasing maintenance costs!

#### Hotbars

Hotbars image-analysis technology dramatically increases the decoding speed of damaged or poorly presented 1-D linear barcodes. It has revolutionized the way



barcodes are located and decoded. As a result, DataMan readers have unprecedented read rates and more time for the decoding phase of code reading thereby **dramatically improving the ability to read badly damaged codes**. This proven technology, used in the full range of



DataMan barcode readers, ensures even the most challenging barcodes found in industrial applications can be read. With Hotbars, the DataMan 50/60L just reads.


## Fast and Easy Setup

The DataMan 50/60 L features a three-position lens and an integrated aimer for easy setup at different working distances. The incredibly small form factor enables the reader to integrate into virtually any new or existing installation.


### **Specifications**

	DATAMAN 50L	DATAMAN 60L	
1-D and Stacked Codes	Yes, oriented, ladder or picket fence, selectable		
Omnidirectional 1-D Codes	No		
Postal Codes	N	0	
2-D Codes	No		
Algorithm	1DMax+ (us	ing Hotbars)	
Image Resolution	752 x 480 (global shutter)		
Image Sensor	1/3" (	IMOS	
Acquisition	Max 6	Max 60fps	
Decode Rate	Max 45/sec		
Lens Options	3-position (45/70/110mm) adjustable		
Trigger	Manual; External: single, burst and continuous Internal: self and presentation		
Aimer	LED		
Discrete Inputs	2, non-isolated		
Discrete Outputs	3, non-isolated		
Status Outputs	4 Multifunctional LEDs (external)	3 Multifunctional LEDs (external beeper available)	
Lighting	Integrated bright field		
Communications	USB and RS-232	Ethernet, USB and RS-232	
Power	5VDC to 24VDC and USB Bus	5VDC to 24VDC	
Power Consumption	500mA @ 24VDC	2.5W	
Material	Aluminum Housing \ Polycarbonate Window		
Weight	76g (w/cable)	100g (3.42 oz)	
Dimensions	23.5mm x 26.5mm x 45.4mm	55mm x 44.5mm x 23.5mm	
Operating Temperature	0°C to 40°C (32°F to 113°F)		
Storage Temperature	-10°C to 60°C		
Operating and Storage Humidity	0% to 95%, non-condensing		
Protection	IP65	IP40	
RoHS Certified	Yes		
Approvals (CE,UL, FCC)	Yes		
Operating System	Microsoft <sup>®</sup> Windows <sup>®</sup> XP an	d Windows 7 32 and 64 bit	

# **Field of View and Reading Distances**







COGNEX Companies around the world rely on Cognex vision and ID to optimize quality, drive down costs and control traceability.

Corporate Headquarters One Vision Drive Natick, MA 01760 USA Tel: +1 508 650 3000 Fax: +1 508 650 3344

Δm	ericas
AIII	ciicas

Americas		
United States, East	+1 50	
United States, West	+1 65	
United States, South	+1 61	
United States, Detroit	+1 24	
United States, Chicago	+1 63	
Canada	+1 90	
Mexico	+52 8	
Central America	+52 8	
South America	+1 90	
Brazil	+554	

1 508 650 3000	
1 650 969 8412	
1 615 844 6158	
1 248 668 5100	
1 630 649 6300	
1 905 634 2726	
52 81 5030 7258	
52 81 5030 7258	
1 909 247 0445	
55 47 8804 0140	

Europe	
Austria	+43
Belgium	+32 2
France	+33
Germany	+49 7
Hungary	+36
Ireland	+353
Italy	+39 (
Netherlands	+312
Poland	+48 7
Spain	+34 9
Sweden	+46 2

700	USA	Ter.	+1:
+43	1 230	60 343	30
+32	2 808	80 692	
+33	1 477	7 1550	)
+49	7216	639 0	
+36	1 501	0650	
+35	3 1 82	25 4420	)
+39	02 67	47 120	00
+31	208 0	80 377	7
+48	71 77	6 0752	2
+34	93 44	5 67 7	8
+46	21 14	55 88	

Switzerland Turkey United Kingdom	+41 71 313 06 05 +90 212 306 3120 +44 1327 856 040	
Asia		
China	+86 21 5050 9922	
India	+9120 4014 7840	
Japan	+81 3 5977 5400	
Korea	+82 2 539 9047	
Singapore	+65 632 55 700	
Taiwan	+886 3 578 0060	
www.cognex.com		

© Copyright 2013, Cognex Corporation. All information in this document is subject to change without notice. All Rights Reserved. DataMan, IDQuick and Cognex are registered trademarks of Cognex Corporation. All other trademarks are property of their respective owners. Lit. No. DM5060DS-1310