

Epson TM-P20 (552): Receipt, BT, Cradle, Adapter, EU

DATASHEET



Reliable printing on the go from Europe's number one POS printer manufacturer¹. The TM-P20 is our smallest, lightest mobile receipt printer ideal for retail staff, hospitality employees, on-board ticketing and anyone who needs receipt printing on the go.

Ultra light and compact

The TM-P20 is under half the size² of our other two-inch model and around two-thirds lighter³. It benefits from fast print speeds (up to 100mm/sec) and a battery life of up to eight hours, making it ideal for busy retail staff dealing with purchases on the shop floor, restaurant staff serving at tables and for producing tickets on-board busses and trains. The device also comes with a belt clip for hands-free transport.

Hassle-free connectivity

Our intelligent ePOS technology can control TM printers directly via web browsers or natively on many smart devices. Near field communication (NFC) functionality allows mobiles and/or tablets to be easily paired with the printers. Barcode pairing is also available for non-NFC devices to make handling faster and easier.

Robust

We know how frustrating delays can be. The TM-P20, therefore, comes with a number of features to help ensure continued operation. To help protect against those little accidents, the device has a drop impact resistance of 150 cm and, together with the optional soft case, it is IP-54 certified for shock and water resistance.

Easy to use

Simple and intuitive operation and LED light indications makes navigating the printer a breeze. Drop-in paper loading means easy paper changes, even on the go.

KEY FEATURES

- **Light and compact**
Ideal for receipt on the go and ticket printing
- **ePOS print**
Allows printing from any mobile device without installing drivers
- **Long battery life**
Lasts up to 8 hours for continued use. (Charger included)
- **NFC and barcode pairing**
Easily pair mobiles or tablets with the printer
- **Fast print speeds**
Up to 100mm/s, for fast receipt printing and transaction

PRODUCT SPECIFICATIONS

Print speed	100 mm/sec
FONTS & STYLES	
Print Speed receipt	100 mm/sec
Print Speed	100 mm/sec
Printing Font	ANK
Printing Font Receipt	ANK
Character set	18 set International
Dot density	203 dpi x 203 dpi
Printing Characters	Text (incl. Euro symbol), Graphics
INTERFACES	
Interfaces	USB 2.0 Type Mini-B, Bluetooth
POWER	
Power Supply	AC adapter, C, Cradle, EURO AC cable
Battery Life	Bluetooth 26 Hours
GENERAL	
Product dimensions	79 x 120 x 44 mm (Width x Depth x Height)
Product weight	0.22 kg
Color	Black (EBCK)
Noise Level	Operation: 57 dB (A)
Installation	horizontally, vertically
Humidity	Operation 10% - 90%
Temperature	Operation -10° C - 50° C
DATA BUFFER	
Data Buffer	0 kB or 128 Bytes
STANDARDS COMPLIANCE	
EMC Standards	FCC class A, CE marking

LOGISTICS INFORMATION

SKU	C31CE14552
Dimensions Single Carton	241 x 192 x 146 mm
Carton Weight	1.4 Kg
Country of Origin	China
Pallet Size Euro	336 Units (48 x 7)

Epson TM-P20 (552): Receipt, BT, Cradle, Adapter, EU

WHAT'S IN THE BOX

- AC adapter, C
- Belt clip
- Cradle
- Main unit
- Roll paper
- USB cable
- User Manual (CD-ROM)
- Warranty document
- Battery (OT-BY20)
- EURO AC cable

OPTIONAL ACCESSORIES

- Epson OT-BY20 (093): Li-Ion Battery for TM-P20 C32C831093
- Epson OT-PC20 (000): Padded Case for TM-P20 C32C881000
- Epson OT-SC20 (002): Single Printer Charger for TM-P20 C32C881002

Available on



For more information please contact:

Telephone: 01952 607111 (UK)+
01 436 7742 (Republic of Ireland)
E-mail: enquiries@epson.co.uk
Chat: etalk.epson-europe.com
Fax: 0871 222 6740
+ Local call rate.

Web: www.epson.co.uk
www.epson.ie

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice.

1. Futuresource consulting, 2010 2. Under half the size is calculated as follows: TM-P20 : 413cm³ / P60II: 1065 cm³, so it is 39% of the volume of the P60II 3. Around a third of the weight is calculated as follows: TM-P20: 228g / P60II: 630g, so it is 36% of the weight of the P60II

EPSON[®]