

Epson TM-T70II-DT Series

DATASHEET



Retailers can streamline operations, save space and reduce costs with the Epson TM-T70II-DT – a unique integrated terminal hub and thermal receipt printer designed to work with the web. Ideal for retailers moving from legacy systems to a full web environment, the TM-T70II-DT has a built-in controller that can seamlessly connect peripheral devices and work as a web server.

The TM-T70II-DT is equipped with an internal web server, a choice of Windows® Embedded POSReady or Linux and ePOS-Device, enabling retailers to take full advantage of web-based applications and thin client solutions. POS peripherals - such as scanners, magnetic stripe readers, customer displays, scales and EFT (electronic funds transfer) terminals – can be conveniently controlled through the web without the need for additional drivers, and connected using the printer's USB ports and VGA port.

Offering retailers significant cost savings, the TM-T70II-DT is a standalone, all-in-one solution that doesn't need a connection to a PC or POS terminal. This reduces the amount of hardware needed, cutting energy usage and reducing maintenance and servicing expenses. The printer's 'paper save' feature lower costs further.

The TM-T70II-DT provides full resilience, with local storage that can be used to back-up POS applications and databases - so if the network becomes disconnected, sales won't stop.

With a stylish, front loading paper design, the TM-T70II-DT can be placed under the counter and is available in a new tone of black color to match the latest mobile devices.

KEY FEATURES

- Front loading paper feed
- No PC or POS terminal needed
- Control peripherals from the web
- Processor and storage for back-up

Epson TM-T70II-DT Series

PRODUCT SPECIFICATIONS

FONTS & STYLES

Column capacity Paper width 80 mm, 56 / 42

PAPER

Paper size 79.50 ± 0.50 (W) mm x dia 83.00 mm,
57.50 ± 0.50 (W) mm x dia 83.00 mm

FONTS & STYLES

Print Speed 250 mm/sec
Printing Font ANK
Column capacity receipt Paper width 80 mm, 56 / 42
Character size 0.99 mm (W) x 2.4 mm (H) / 1.41 mm (W) x 3.39 mm (H)
Character set 95 Alphanumeric, 18 set International, 128 x 43 Graphic
Dot density 180 dpi x 180 dpi
Color Printing Single Color

INTERFACES

Interfaces Ethernet interface (100 Base-TX / 10 Base-T), USB 2.0 Type A (6x), RS-232, VGA out, Stereo mini jack audio out, Drawer kick-out

DATA BUFFER

Data Buffer 4 kB or 45 Bytes

GENERAL

Product dimensions 172 x 290 x 114 mm (Width x Depth x Height)
Product weight 2.8 kg
Installation horizontally
Humidity Operation 10% - 90%, Storage 10% - 90%
Temperature Operation 5° C - 45° C, Storage -10° C - 50° C

STANDARDS COMPLIANCE

EMC Standards CE marking, EN55022 Class A
Safety standards TÜV

OTHER FEATURES

CPU Atom N2600 1.6GHz, Atom N2800 1.86GHz
Preloaded SW WebPOS Config, ePOS-Device®
Sensors Unit open sensor, Paper End Sensor, Paper Near End Sensor

OTHER

Warranty 12 months Carry in

LOGISTICS INFORMATION

Dimensions Single Carton 400 x 250 x 278 mm

Carton Weight 4.5 Kg

WHAT'S IN THE BOX

- AC Adaptor
- Cable cover
- Main unit
- Paper roll spacer
- Thermal roll paper

OPTIONAL ACCESSORIES

- Epson OT-WL01 (732): Wireless LAN set for Epson TM-i C32C890732

For more information please contact:

Telephone: 0871 222 6702 (UK)+
01 436 7742 (Republic of Ireland)
E-mail: enquiries@epson.co.uk
Fax: 0871 222 6740

Web: www.epson.co.uk
www.epson.ie

1. Source: Interconnection Consulting, 2010.

+ Calls cost 10p per minute plus network extras.

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice.

EPSON®