

# Getac

Rugged Mobile Computing Solutions



## RX10 Fully Rugged Tablet

- Intel® Core™ M vPro™ Processor Technology
- 10.1" Full HD LumiBond®2.0 display with Getac sunlight readable technology
- Getac proprietary SnapBack accessories with keyboard & SmartCard options
- 1D/2D imager barcode reader option
- LifeSupport™ hot-swap battery technology for uninterrupted power



SnapBack Add-on



Office Dock



# RX10 Fully Rugged 10.1" Tablet

Getac recommends Windows.



## Specifications

<b>Operating System</b>	Windows 7 Professional Windows 10 Professional
<b>Mobile Computing Platform</b>	Intel® Core™ M Processor Technology  Intel® Core™ M 1.2GHz Processor (up to 2.90 GHz with Intel® Turbo Boost Technology) - 4M Intel® Smart Cache  Intel® Core™ M 800MHz Processor (up to 2 GHz with Intel® Turbo Boost Technology) - 4M Intel® Smart Cache
<b>Graphics</b>	Intel® HD Graphics 5300
<b>Display</b>	10.1" TFT LCD Full HD LumiBond®2.0 display with Getac sunlight readable technology capacitive multi-touch screen (1920 x 1200, 800nits)
<b>Memory &amp; Storage</b>	4GB LPDDR3 (expandable to 8GB) SSD 64GB / 128GB
<b>Keyboard</b>	6 tablet buttons (Windows, Power, Function Key 1, Function Key 2, Barcode Reader Trigger, Volume Up, Volume Down)
<b>Pointing Device</b>	Touchscreen - Capacitive multi-touch screen - Optional dual mode touchscreen (multi-touch and digitizer)
<b>Expansion Slot</b>	Optional 1D/2D imager barcode reader
<b>I/O Interface</b>	HD webcam x 1 8M pixels auto focus rear camera x 1 Headphone out/mic-in combo x 1 DC in Jack x 1 USB 3.0 (9-pin) x 1 USB 2.0 (4-pin) x 1 Docking connector (16-pin) x 1 Micro HDMI x 1 Optional RF antenna pass-through for GPS, WLAN and WWAN
<b>Communication Interface</b>	Intel® Dual Band Wireless-AC 7265, 802.11ac Bluetooth (v4.0 class 1) <sup>i</sup> Optional dedicated GPS Optional Gobi™ mobile broadband

<b>Software</b>	Getac Utility Getac Camera Adobe® Reader® Getac Barcode Manager Optional CompuTrace® Persistence module
<b>Security Feature</b>	TPM 2.0 Optional Intel® vPro™ Technology Optional fingerprint scanner or RFID reader <sup>ii,iii</sup> Optional SnapBack add-on : Hand Strap & Kick Stand & Smart Card Reader Optional SnapBack add-on : Hand Strap & Kick Stand & Smart Card Reader & Detachable Keyboard
<b>Power</b>	AC adapter (65W, 100-240VAC, 50 / 60Hz) Li-Ion battery (15.2V, 2160mAh) <sup>iv</sup> LifeSupport™ hot-swap battery technology
<b>Dimension (W x D x H) &amp; Weight</b>	280x 245 x 18.8mm 1.2 ~ 1.3kg <sup>v</sup>
<b>Rugged Feature</b>	MIL-STD-810G certified and IP65 certified 4 feet drop resistant Vibration & drop resistant e-Mark certified for vehicle usage Optional ANSI/ISA 12.12.01 Optional EN/IEC 60601-1
<b>Environmental Specification</b>	Temperature <sup>vi</sup> : - Operating: -21°C to 55°C - Storage: -40°C to 71°C Humidity: - 95% RH , non-condensing
<b>Optional Accessories</b>	Carry bag Main battery (15.2V, 2160mAh) AC adapter (65W, 100-240VAC) Vehicle adapter (90W, 11-16V DC and 22-32V DC) Capacitive stylus & tether Digitizer pen Shoulder strap (2-point) Hand-strap & Kick Stand Hand-Strap & Kick Stand & Smart Card Reader Hand-Strap & Kick Stand & Smart Card Reader & Detachable Keyboard Vehicle dock Office dock Protection Film Multi-Bay Charger (Two Bay) Multi-Bay Charger (Eight Bay)

## Docking Solutions

	Serial Port	External VGA	DC in Jack	USB	LAN	HDMI	RF Antenna Connector
<b>Vehicle Dock</b>	1	-	1	2	1	-	3 (Optional)
<b>Office Dock</b>	-	1	1	4	1	1	-

<sup>i</sup> Bluetooth performance and connectable distance may be subject to interference from the environment and other client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that are operating in the area.

<sup>ii</sup> RFID and Fingerprint scanner are mutually exclusive options.

<sup>iii</sup> 13.56MHz Contactless RFID/NFC reader (ISO 15693, 14443 A/B, Mifare and FeliCa™ compliant).

<sup>iv</sup> Battery life testing conducted under MobileMark 2007. Battery performance will vary dependant upon

software applications, wireless settings, power management settings, LCD brightness, customized modules and environmental conditions. The battery has a limited number of charge cycles and may eventually need to be replaced by a Getac service provider. Battery life and charge cycles vary by use and settings.

<sup>v</sup> Weight varies from configurations and optional accessories.

<sup>vi</sup> Tested by an international independent third party test lab following MIL-STD-810G.

# Getac



**Getac UK Limited**  
Mitac House, Nedge Hill, Telford,  
Shropshire, TF3 3AH, U.K.  
Tel: +44 1952 207 231  
Email: sales-getac-UK@getac.com  
www.getac.co.uk