



Wax/Resin PM308

Wax/Resin PM308

Outstanding versatility
and durability.

Hybrid wax/resin delivers exceptional print quality and abrasion resistance on a wide range of paper and mid-range synthetic label stocks. Produces sharp, clear text and barcode lines for maximum readability and can be used in outdoor applications.

Benefits

- Prints on a broad range of substrates including both rough and smooth surfaces
- Crisp character and line formation with dark solid fills
- Stands up to rough handling, abrasion and outdoor elements
- Compatible print energy requirements, no energy adjustments
- Anti-static formula and specially formulated backcoat protects the printhead
- Clean Start® built-in printhead cleaner

Recommended Stocks

- Matte, semi gloss, high gloss paper
- Polypropylene
- Polyethylene



The printhead cleaner *built in* your ribbon.

IIMAK Thermal Transfer Ribbons

PM 308	Prime Mark	SP330
Wax/Resin High durability to endure rough handling, abrasion, occasional chemical exposure and outdoor elements		Resin Maximum durability to resist abrasion, heat, steam, and chemicals

Wax Ribbons for General Purpose Labeling
GP725 | High Mark

Ribbons for Near Edge Printers and Flexible Packaging Coders
NET FLEX | NET MARK IQ | NET RESIN IQ

Color Thermal Transfer Ribbons
DC100 | DC200 | DC400 | NET Color

Security Enhanced Thermal Transfer Ribbons
UV Invisible



310 Commerce Drive • Amherst, NY 14228
Toll-Free: 888.464.4625 • Phone: 716.691.6333
salesinfo@iimak.com • www.iimak.com



Applications



Industrial



Outdoor



Horticulture



Lumber



Shipping



Pharmaceutical



Shelf/Bin



Pallet

PM308 Wax/Resin

Crisp, clear thermal images with high durability for a wide range of premium labeling applications. Versatile ink prints on rough and smooth papers and synthetics.



Imaging Characteristics

Printer	Print Speed	Energy Range
Flathead	8 IPS	Mid

Image Darkness	Scratch/Smudge	Chemical
1.7 RD (densitometer)	Mid-Range Resistance	Low to Moderate Resistance



Technical Specifications

Color Code Tab..... Teal
 Film Thickness..... 4.5 Microns
 Total Ribbon Thickness..... 8.4 Microns
 Transmission Density..... 2.60 MacBeth Scale
 Ink Melting Point..... 65°C/149°F

Sample PM308 Ribbons

Part # CES11027 – 110 mm x 50 m – CSI
 Part # CES11026 – 110 mm x 50 m – CSO

Typical Compliance

- REACH – SVHC Free
- RoHS/WEEE
- TSCA
- CONEG
- California Proposition 65
- Additional Regulatory Requirements Upon Request

Industry Leading Customer Service

- Free Clean Start® built-in printhead cleaner
- Free samples
- Free technical support 888.372.0137
- Free 24-hour print tests
- Over 500 SKUs stocked for same-day shipping
- Complete line of over 2,000 SKUs



310 Commerce Drive • Amherst, NY 14228
 Toll-Free: 888.464.4625 • Phone: 716.691.6333
 salesinfo@iimak.com • www.iimak.com
 Thermal Transfer Ribbons made in the USA