



Standard Wax SW150



SW150 Standard Wax

Economical printing with consistent performance

A pure wax ribbon suitable for standard applications. SW150 provides a reliable solution for very short-lived, basic high volume applications typically found in shipping or Work-in-Progress (WIP) tracking. A simple single layer of wax performs well on rough, uncoated and coated papers. SW150 prints normal and rotated barcodes, small text and provides acceptable blackness for most applications.

Benefits

- Handles basic applications with ease
- Reliable, economical wax ink
- Good print quality on low end paper tag and label stocks
- High wax content allows for lower printer darkness settings
- Print speeds up to 8 IPS

Recommended Stocks

- Uncoated paper & label stocks
- Coated paper & label stocks

Sample SW150 Ribbons

Part # CES11031- 110 mm x 50 m - CSI

Part # CES11030 - 110 mm x 50 m - CSO

Applications



Shipping



WIP Tracking



Retail



MADE IN USA

Technical Specifications

Film Thickness..... 4.5 Microns

Total Ribbon Thickness..... 7.4 Microns

Transmission Density..... 1.73 MacBeth Scale

Ink Melting Point..... 67°C/152°F

Imaging Characteristics

Printer..... Flathead

Max Print Speed..... 8 IPS (200 mm/s)

Energy Range..... Low-Mid

Image Darkness..... 1.35 RD (densitometer)

Scratch/Smudge..... Low-Mid Resistance

Compliance

- REACH – SVHC Free
- RoHS/WEEE
- TSCA
- CONEG
- California Proposition 65
- Additional Regulatory Requirements Upon Request

RESIN

SP330
SP575
DC400 Color

WAX
RESIN

Prime Mark
PM308
DC200 Color

WAX

GP725
High Mark
SW150
DC100 Color

NEAR
EDGE

NET Resin IQ
NET Mark IQ
NETFlex+
NETColor

310 Commerce Drive • Amherst, NY 14228

Toll-Free: 888.464.4625 • Phone: 716.691.6333 • salesinfo@iimak.com • www.iimak.com