### Technology at Work.®





## **XG Series**

### For the Work at Hand.

Janam's XG Series is optimized to meet the unique requirements of mobile workers in warehouses, distribution centers, loading docks and other operating venues where rugged gun-shaped mobile computers are deployed. The products' rugged industrial-grade construction enables full functionality in the most hostile operating environments, and its sleek upper body creates a wide profile for larger keys without adding unnecessary weight or bulk. The powerful battery is in the handle. This unique design makes the XG100 and XG105 incomparably light and balanced in the hand, making them ideal for scan-intensive, extended shift use in demanding environments.

### Winning Form Factor. Winning Features.

The XG Series offers mobile workers an unmatched combination of highly functional design and optimized human interface. The Series includes the XG100 with Honeywell's Adaptus® imaging technology and the XG105 with Motorola's SE965 high-performance laser scan engine. The rugged handhelds are sealed to IP64 and withstand multiple 6' drops to concrete. With mobile double data rate (DDR) memory and 7.4V 2500 mAh batteries, the XG100 and XG105 deliver best-in-class computing speed and battery life. Designed for the work at hand, the XG100 and XG105 deliver superior performance and flexibility at a great price.

# 

### The XG Series delivers at every level:

### **Worker Productivity**

- » Unique design makes it incomparably light and balanced in hand
- » Laser for distance scanning and hard to read barcodes or imager for fast, convenient 1D and 2D omnidirectional barcode data capture
- » Large, well spaced keys that are easy to locate, easy to press
- » 3.7" VGA display and extra-bright keypad backlight
- » Vibrator alert for successful scan notification in noisy environments
- » Bright LED tail lights for visual feedback during overhead scanning

### **Tough Environments**

- » Withstands multiple 6' drops to concrete on all six sides across full temperature range
- » Survives 2,000 tumbles (equivalent to 4,000 drops)
- » Sealed to IP64 standards
- » All keys tested to 1,000,000 actuations
- » Built-in battery thermistor stops charging in overheated conditions

### **Easy Migration, Easy Integration**

- » Robust Summit WiFi radio, Aruba Networks and Cisco certified
- » Integrated Electronic Article Surveillance (EAS) tags for enhanced asset protection
- » Emulator keypads insuring compatibility with existing installations
- » Full suite of single-slot and four-slot cradles designed for every communication protocol

# XG Series Specifications (XG100 and XG105)



TECHNICAL				
Operating System	Microsoft Windows Mobile 6.1			
Processor	Marvell PXA320 @624MHz			
Memory	256MB DDR SDRAM, 256MB NAND Flash ROM			
Expansion	User accessible microSD card slot			
Power	Removable, rechargeable 7.4V 2500mAh Li-ion; hot swap and orderly shutdown; 80mAh Ni-MH backup battery			
PHYSICAL				
Dimensions	7.24" H x 3.51" W x 9.07" L / 18.4cm H x 8.9cm W x 23.0cm L			
Weight (with battery)	24.3oz / 689g (XG100); 24.4oz / 692g (XG105)			
Keypad	Backlit 42-key and 52-key including terminal emulation keypads (5250, 3270, VT)			
Display	3.7" Color TFT VGA; 262K colors			
Touch Panel	Analog resistance type; stylus input			
ENVIRONMENTAL				
Operating Temperature	14° to 122°F / -10° to 50°C			
Storage Temperature	-40° to 158°F / -40° to 70° C			
Humidity	5% to 90% RH (no condensation)			
Drop	Multiple 6ft /1.8m drops to concrete on all sides across a wide temperature range			
Tumble	2,000 tumbles at room temperature (4,000 hits)			
Water & Dust	IP64 per IEC Sealing Specification			
Vibration	0.03 G <sup>2</sup> /Hz from 20Hz to 2kHz; 1 hour random wave per axis			
Electro Static Discharge (ESD)	+/- 15kVDC air; +/- 8kVDC contact	·		
INTERFACE FEATURES				
Audio	Speaker and microphone			
Alerts	Vibration, LED indicators, full audio			
LED Indicators	Tri-color indicators at top, rear and bottom			
Scan Triggers	Pistol-grip trigger (located on handle)			
DATA CAPTURE				
Imager (XG100)	Honeywell Adaptus Imaging Technology; 752 x 480 pixel CMOS area imager; 1D ready, 2D capable with firmware upgrade			
Laser (XG105)	Motorola SE965HP; CDRH Class III	EC Class 2; 104 (± 12) scan/sec (bidirectio	nal)	
DATA COMMUNICATION				
WLAN	Summit IEEE 802.11b/g; Aruba Networks certified; Cisco certified			
WLAN Security	WPA-PSK, WPA2-PSK, AES, LEAP, PEAP (MS-CHAPv2), PEAP-TLS, TKIP, EAP-TLS, WEP 40-bit, WEP 128-bit			
	WPA-PSK, WPA2-PSK, AES, LEAP, P	EAP (MS-CHAPv2), PEAP-TLS, TKIP, EAP-TLS	, WEP 40-bit, WEP 128-bit	
	WPA-PSK, WPA2-PSK, AES, LEAP, P Bluetooth v2.0	EAP (MS-CHAPv2), PEAP-TLS, TKIP, EAP-TLS	, WEP 40-bit, WEP 128-bit	
WPAN		EAP (MS-CHAPv2), PEAP-TLS, TKIP, EAP-TLS	, WEP 40-bit, WEP 128-bit	
WPAN USB	Bluetooth v2.0	EAP (MS-CHAPv2), PEAP-TLS, TKIP, EAP-TLS	, WEP 40-bit, WEP 128-bit	
WPAN USB	Bluetooth v2.0	EAP (MS-CHAPv2), PEAP-TLS, TKIP, EAP-TLS Syncing/Charging Cables	, WEP 40-bit, WEP 128-bit  Adjustable Handstrap	
WPAN USB	Bluetooth v2.0 v2.0 client (full speed), v2.0 host			
WPAN USB	Bluetooth v2.0 v2.0 client (full speed), v2.0 host Single-Slot Cradle Kits	Syncing/Charging Cables	Adjustable Handstrap	
WPAN USB ACCESSORIES	Bluetooth v2.0 v2.0 client (full speed), v2.0 host Single-Slot Cradle Kits Four-Slot Cradle Kits	Syncing/Charging Cables DEX Cable	Adjustable Handstrap Stylus 5-Pack	
WPAN USB ACCESSORIES SAFETY/REGULATORY	Bluetooth v2.0 v2.0 client (full speed), v2.0 host Single-Slot Cradle Kits Four-Slot Cradle Kits Battery Charger Kit	Syncing/Charging Cables DEX Cable	Adjustable Handstrap Stylus 5-Pack Holster	
WPAN USB ACCESSORIES  SAFETY/REGULATORY Safety	Bluetooth v2.0 v2.0 client (full speed), v2.0 host Single-Slot Cradle Kits Four-Slot Cradle Kits Battery Charger Kit UL60950-1, CSA C22.2 No. 60950	Syncing/Charging Cables  DEX Cable  Stylus Tether  1, EN/IEC60950-1, IEC60825-1, Laser Clas	Adjustable Handstrap Stylus 5-Pack Holster s 2+CDRH	
WEAN SCEUITY WPAN USB ACCESSORIES  SAFETY/REGULATORY Safety EMI RF	Bluetooth v2.0 v2.0 client (full speed), v2.0 host Single-Slot Cradle Kits Four-Slot Cradle Kits Battery Charger Kit UL60950-1, CSA C22.2 No. 60950	Syncing/Charging Cables  DEX Cable  Stylus Tether  1, EN/IEC60950-1, IEC60825-1, Laser Class B (CE:EMC), EN55024 (CE:EMC), ICES-003	Adjustable Handstrap Stylus 5-Pack Holster s 2+CDRH	