



## OUTDOOR DUAL RADIO 802.11A/B/G/N MESH WIRELESS ACCESS POINT

# AP 6562

Designed for extending Wi-Fi coverage to outdoor areas, the AP 6562 provides a cost-effective means of supporting the most demanding wireless applications and large number of wireless devices. Ideal for distribution centers, hospitality, retail, and education campuses, the AP 6562 can handle the increasing number of Wi-Fi enabled devices and bandwidth heavy applications connecting to your wireless network.

The AP 6562 access point is designed to help lower the cost of deploying and operating a secure, reliable, and targeted outdoor wireless network, all powered by the WiNG 5 architecture. Choose from two models: an integrated antenna model for fast wall mounting or an external antenna model for pole mounting and remote wireless backhaul. The access point features dual 802.11n 2x2 radios with superior receive and transmit performance, a console port for configuration, and a GiGE LAN/WAN POE-enabled port for local or remote network connectivity. With its WiNG 5 intelligence, this access point seamlessly extends your network to the outdoors with higher throughput along with direct forwarding, security, QoS services and site survivability.

### INTELLIGENT MESH NETWORKING

To enable the extension of wireless network coverage to areas where Ethernet cabling is cost-prohibitive or otherwise impractical, the AP 6562 can operate wirelessly, connecting to other access points for data backhaul, in a mesh topology. The AP 6562 provides robust data connections throughout the network by leveraging Motorola's MeshConnex™. MeshConnex provides efficient routing, low latency, low routing overhead, high-speed handoffs and proven scalability. The AP 6562 delivers superior performance in hotels and resorts covering pool areas, in retail environments covering parking lots, outdoor yards in distribution centers, and education campus outdoor areas.

### HIGH PERFORMANCE DUAL-RADIO DESIGN

The AP 6562 is an independent, dual radio access point designed to lower the cost of deploying and operating a secure, reliable 802.11n wireless LAN outdoor. The AP 6562 features dual MIMO radios with superior receive and transmit sensitivity.

One radio can be used for client access while the second radio is used for simultaneous client access on a different frequency band or as a dedicated sensor for security and troubleshooting. The AP 6562 is a site survivable wireless access point that does not require a controller and can act as a virtual controller coordinating the activities of 24 neighboring access points.

### GAP-FREE SECURITY

The AP 6562 provides enterprise-class security with layer 2-7 stateful packet filtering firewall, AAA RADIUS services, Wireless IPS-lite, VPN gateway, and location-based access control. The security capability of the AP 6562 is further enhanced when deployed in combination with premise or cloud-based versions of the AirDefense Services Platform, which increase the security and resiliency of AP 6562 networks with an array of advanced security and network assurance features including Spectrum Analysis, Wireless IPS, Live RF, Advanced Forensics and AP Testing to proactively identify and mitigate network disruptions.

### LESS IS MORE

Motorola's WiNG 5 WLAN solutions offer all the benefits of 11n—and then some. Our distributed architecture extends QoS, security and mobility services to the APs so you get better direct routing and network resilience. That means no bottleneck at the wireless controller, no latency issues for voice applications, and no jitter in your streaming video. And with our broad selection of access points and flexible network configurations, you get the network you need with less hardware to buy. Let us show you the less complicated, less expensive way to more capacity, more agility, and more satisfied users.

**PRODUCT SPEC SHEET**  
AP 6562

**IMPROVE YOUR GUEST EXPERIENCE**

Deploying a simple outdoor extension to the indoor wireless network comes naturally with AP 6562, allowing hospitality customers the ability to reach outdoors with applications targeted toward guest experience and concierge, expedited check-in and valet, or toward revenue generation in pool and guest access areas.

**FAST AND EASY ZERO-TOUCH DEPLOYMENT**

The AP 6562 requires no configuration or manual firmware maintenance. The Motorola wireless controller discovers access points on the network and automatically downloads all configuration parameters and firmware, greatly reducing installation, maintenance and troubleshooting costs for Layer 2 and Layer 3 deployments. With internal and external antenna SKU options, the compact and aesthetic design provides more choices for mounting locations.

**FEATURES**

**Ideal Applications**

- Hospitality
- Enterprise, Education and Healthcare campus facilities
- Manufacturing and Logistics
- Retail Outdoor Spaces
- Service Providers and Hotspot Deployments

**Full 802.11n performance with standard 802.3at**

Simplifies and reduces total cost of installation using standard Power-over-Ethernet (PoE)

**Mobility**

Supports fast secure roaming

**Security**

This unique multi-purpose device can execute and enforce the IDS/IPS security policies configured in the Motorola wireless switch, and can also be utilized as a 24x7 dedicated sensor for Wireless IPS with AirDefense Services Platform

**Mesh networking**

Patented Mesh Networking—MeshConnex™ allows wireless extension of existing wired or wireless networks in remote or outdoor locations. Eliminates running expensive cables to every AP outdoors

**Outdoor rated IP 67 Cast Aluminum Enclosure**

Equipment designed to withstand wind, rain, and extreme temperatures

**AP 6562 SPECIFICATIONS CHART**

PHYSICAL CHARACTERISTICS	AP 6562 (INTERNAL ANTENNA)	AP 6562 (EXTERNAL ANTENNA)
Dimensions:	9.1" W x 9.8" H x 2.6" D	9.1" W x 9.8" H x 2.6" D
Weight:	2.9 lbs	2.9 lbs
Part number:	AP-6562-66030 (- US, -WR, -EU)	AP-6562-66040 (- US, -WR, -EU)
Mounting configurations:	Adaptable mounting kit for wall & pole deployments (KT-147407-01) -01 With optional extension arm accessory (KT-150173-01)	

**WIRELESS DATA COMMUNICATIONS AND NETWORKING**

Data rates supported:	802.11b/g: 1,2,5.5,11,6,9,12,18,24,36,48, and 54Mbps 802.11a: 6,9,12,18,24,36,48, and 54Mbps 802.11n: MCS 0-15 up to 300Mbps
Network standard:	802.11a, 802.11b, 802.11g, 802.11n
Wireless medium:	Direct Sequence Spread Spectrum (DSSS) and Orthogonal Frequency Division Multiplexing (OFDM), and Spatial Multiplexing (MIMO)
VLANs/WLANs supported:	VLANs and WLANs are controller-dependent
Uplink:	Auto-sensing 10/100/1000Base-T Ethernet

**RADIO CHARACTERISTICS**

Operating channels:	<b>Radio 1:</b> 2.4GHz: Chan 1-13 (2412-2472 MHz), Chan 14 (2484 MHz) Japan only <b>Radio 2:</b> 2.4GHz: Chan 1-13 (2412-2472 MHz), Chan 14 (2484 MHz) Japan only 5GHz: All channels from 5200 MHz to 5825 MHz Actual operating frequencies depend on national regulatory limits
Maximum available transmit power:	2.4GHz: 21dBm per chain, 5.0GHz: 20dBm per chain
Transmit power Adjustment:	1dB increment
Antenna configuration:	1x1, 1x2, 2x2
Operating bands:	2412 to 2472 MHz and 2484 MHz, 5180 to 5825 MHz

**USER ENVIRONMENT**

Operating temperature:	-30 to +60°C
Storage temperature:	-40 to 85°C
Operating humidity:	5 to 95% RH, non-condensing
Operating altitude:	8,000 ft
Storage altitude:	30,000 ft
Electrostatic discharge:	EN61000-4-2, Air +/-15kV, Contact +/-8kV
Enclosure:	Outdoor IP67 rated, Polymeric corrosion resistant enclosure ASTM B117 Salt, Fog, and Rust resistance
Operational shock:	IEC60721-3-4, Class 4M3, MIL STD 810F
Operational vibration:	IEC60721-3-4, Class 4M3

**POWER SPECIFICATIONS**

Operating voltage:	36-57 VDC
Power in (PoE):	802.3at

**MAXIMUM RADIO TRANSMIT POWER:**

BAND	SINGLE ANTENNA TRANSMIT POWER	DUAL ANTENNA COMPOSITE TRANSMIT POWER
2400MHZ	+21 dBm	+24 dBm
5200MHZ	+20 dBm	+23 dBm

**INTERNAL ANTENNA INFORMATION**

INTERNAL ANTENNA DESCRIPTION	VALUES
Radio 1: 2.4GHz band	5.0 dBi
Radio 2: 2.4GHz band	3.0 dBi
Radio 2: 5.0GHz band	6.0 dBi

**REGULATORY**

Product safety certifications:	UL 60950, cUL, EU EN 60950, TUV and UL 2043 (external antenna)
Radio approvals:	FCC (USA), Industry Canada, CE (Europe) and TELEC pending (Japan)

**OPTIONAL ACCESSORIES**

Mounting Kit, Extension Arm for Mounting Kit, IP66 Outdoor Rated 802.3AT Power Injector, Mounting Kit for Outdoor IP 66 802.3AT Power Injector, External Antenna Options

**WARRANTY**

One (1) year on AP 6562 hardware \*accessories not included, (30) Day on Accessories, (90) Day on Software

**PRODUCT SPEC SHEET**

AP 6562

For more information on how the AP 6562 can benefit your business, please visit us on the web at [www.motorolasolutions.com/wlan](http://www.motorolasolutions.com/wlan) or access our global contact directory at [www.motorolasolutions.com/enterprisemobility/contactus](http://www.motorolasolutions.com/enterprisemobility/contactus)

Part number: SS-AP6562. Printed in USA 01/13. MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. ©2013 Motorola Solutions, Inc. All rights reserved. Specifications are subject to change without notice.

