

## Small, Durable and Easy to Connect

Increase productivity and reduce data errors in mobile business applications with the Socket Bluetooth Cordless Hand Scanner (CHS), a wireless barcode reader for smartphones and tablets that's small, portable and provides fast, industrial-class scanning performance.



- **Designed for Mobility** - Small, light, and portable with 19-hours battery life
- **Comfortable** - Ergonomic for comfortable use over extended periods
- **Easy to Connect** - Simply scan a barcode on the screen to quickly pair devices.

### Hardware Features

- Easily connect to Bluetooth enabled smartphones, tablets, PDAs, notebooks and desktop computers:
  - Apple iOS
  - Android OS
  - Windows 8, RT, 7, Vista, XP
  - Windows Embedded Handheld (Windows Mobile)
  - BlackBerry OS, QNX, Linux
  - Mac OS
- Class 1 Bluetooth 2.1 + EDR provides secure, long-range wireless connection up to 330 ft (100 m)
- Battery Friendly® technology enables extensive 19-hour battery life on a single charge
- Apple iOS certified to add support for Bluetooth SPP connections with iPad, iPhone, iPod touch (Requires SDK or compatible app developed with SDK)
- Extra durable exterior casing withstand multiple 6.6 ft (2m) drops to concrete. Watch video at: <http://www.youtube.com/watch?v=fSAeVdiUUXE>
- White antimicrobial version for healthcare, food service & other hygiene-sensitive work environments
- Easy to use with automatic reconnections
- LED and beeps indicate good scan, connection, and power status
- Vibrate mode for good scans, great for noisy worksites where beeps are hard to hear or noise-sensitive applications where beeps must be disabled
- Quickly access Apple iOS on-screen keyboard with special "double press" scanner button feature
- Supports Bluetooth HID connections for easy setup with no software installation<sup>1</sup>
- Supports Bluetooth SPP connections for advanced scanner control<sup>2</sup>

### Software Features (SPP mode only)

- SocketScan™ 10 keyboard wedge software enters scanned data into any application -- no custom programming needed
- Socket EZ Pair automates Bluetooth setup for maximum ease of use
- Suffix support: automatically add a carriage return or tab after each scan of data
- Software utility enables you to configure beep, LED and vibrate settings, enable / disable symbology (barcode type) and monitor scanner battery level
- Determine the symbology or length of a barcode
- SocketScan 10 SDK available with subscription to Socket Mobile Developer Program (\$19.95 / year) <http://www.socketmobile.com/support/Developer/>

<sup>1</sup>HID not supported for BlackBerry OS or iPhone 3G

<sup>2</sup>SPP not supported for Mac OS or QNX. For iOS support with Bluetooth SPP, the SDK or a compatible app is required.

	<p><b>CHS 7Di and 7DiRx</b> Ideal for field sales and field service, the CHS 7Di is durable to withstand multiple drops to concrete, with a protective rubber bumper and rubber sealings. The CHS 7DiRx is a white antimicrobial version for healthcare.</p>
	<p><b>CHS 7Pi</b> For Special Lighting Conditions or Barcode Requirements Featuring a Class 2 laser, the CHS 7Pi work well in bright sunlight, in low light, as well as with barcodes that are small, tightly spaced, on shiny surfaces or behind plastic / glass.</p>
	<p><b>CHS 7Xi and 7XiRx</b> High performance for scanning 2D and 1D barcodes, printed or on-screen. Reads barcodes displayed on screen of smartphone, laptop, tablet, etc. Extra durable for outdoor use or fast, demanding operations.</p>

CHS Model	7Di	7DiRx	7Pi	7Xi	7XiRx
Scanner SKU #	Gray: CX2877-1472	Antimicrobial: CX2879-1474	Gray: CX2874-1413	Gray: CX2864-1336	Antimicrobial: CX2866-1338
Dimensions / Total Mass	5.2 X 1.77 X 1.49 in. (132 x 45.1 x 37.9 mm)				
Drop Specification	Extra durable exterior case withstands multiple 6.6 ft (2 m) drops to concrete				
Temperature	Operating Temperature: +32 to +122°F (0 to + 50°C) Storage Temperature: -22 to + 158°F (-30 to + 70°C) Ranges may vary with battery shelf life.				
Relative Humidity	5% to 95% non-condensing				
Ambient Light	0 - 110,000 lux				
Antimicrobial Rating (JIS Z2801:2000 Test) Biosafe HM4100, EPA# 83019-1	N/A	2.49 on MRSA 6.07 if cleaned with Sani-Cloth Plus cloth wipes	N/A	N/A	2.49 on MRSA 6.07 if cleaned with Sani-Cloth Plus cloth wipes
Battery Type	Two AAA NiMH rechargeable batteries			One Lithium ion rechargeable battery	
Battery Life	14 hours			10 hours	
Scanner type	Imager (1D)		Laser (1D)	Omni-Directional Imager (2D)	
Scan Barcodes on Device Screens	✓	✓		✓	✓
Direct Part Marking (DPM) Support	✓	✓	✓	✓	✓
Vibrate Mode for Good Scans	✓	✓	✓	✓	✓
Symbologies Decoded	Bookland EAN (ISBN / EAN-13), Chinese 2 of 5, Codabar, Code 11, Code 128, Code 39, Code 93, Discrete 2 of 5, GS1 DataBar (RSS), GS1-128 (UCC-128/EAN-128), Interleaved 2 of 5 (ITF-14), MSI, Plessey, UPC/EAN, UPC/EAN/JAN supplemental redundancy, Coupon Report, ISSN EAN, Inverse 1D, ISBT concatenations, Matrix 2 of 5		Bookland EAN (ISBN / EAN-13), Chinese 2 of 5, Codabar, Code 11, Code 128, Code 39, Code 93, Discrete 2 of 5, GS1 DataBar (RSS), GS1-128 (UCC-128/EAN-128), Interleaved 2 of 5 (ITF-14), MSI, Plessey, UPC/EAN	1D: Bookland EAN (ISBN / EAN-13), Codabar (including ISBT 128 bit concatenation), Code 11, Code 128, Code 39, Code 93, Discrete 2 of 5, GS1 DataBar (RSS), GS1-128 (UCC-128/EAN-128), Interleaved 2 of 5 (ITF-14), MSI, Plessey, UPC/EAN 2D: Aztec, Codablock, Data Matrix, GS1 (EAN.UCC), Matrix 2 of 5, Maxicode, PDF 417, Macro PDF 417, Micro PDF 417, QR Code, Standard 2 of 5, Telepen, TLCode 39 Postal: Australia Post, BPO 4, Canada Post, Dutch Post (KIX), Japan Post, Planet, Postnet, RM4SCC, Sweden Post, TLCode 39, 4 State Code, USPS Intelligent Mail	
Scan Repetition Rate	5 scans/sec		5 scans/sec bi-directional	Omni-Directional / Auto-Adaptive 5 images / second	
Optical Resolution	5 mil minimum		0.004 inch (0.102mm) min./barcode element width	752(H) x 480(V) pixels, 256 gray levels	
Print Contrast	Minimum 20%		Minimum 25% MRD at 650 nm	Down to 25%	
Scan Angle	53.3° ± 3°		Wide (default): 47° ± 3° Narrow: 35° ± 3°	Horizontal: 38.9° Vertical: 25.4°	
Decode Distance <sup>3</sup>	5.7 to 50.8 cm (2.25 to 20 in.)		3.8 to 114+ cm (1.5 to 45+ inches)	4.8 to 40.6 cm (1.9 to 16 in.) Depends on symbol size, symbology, label media, W-N ratio, scan angle.	
Bluetooth Profile Support	Human Interface Device (HID) and Serial Port Profile (SPP) Some OS versions or smartphone/tablet models support only one profile.				
Bluetooth Version	Bluetooth 2.1 + EDR (Enhanced Data Rates) with 56 bit data encryption				
Radio Range	Up to 100 m (330 ft), depending on environment, range limit is usually due to the Master Device (Phone, Tablet or Notebook)				
OS Support					
Apple iOS	✓	✓	✓	✓	✓
Android OS	✓	✓	✓	✓	✓
Blackberry OS	✓	✓	✓	✓	✓
Windows 8, RT, 7, Vista, XP	✓	✓	✓	✓	✓
Windows Embedded Handheld, Mobile, CE	✓	✓	✓	✓	✓
Mac OS	✓	✓	✓	✓	✓
SocketScan™ 10 Software	Keyboard wedge software featuring Socket EZ Pair for Android, BlackBerry, Windows. Scanner Settings configuration utility also included.				
SocketScan 10 SDK	For Apple iOS, Android, BlackBerry, Windows. Available to members of Socket Mobile Developer Program (\$19.94/year) <a href="http://developer.socketmobile.com">http://developer.socketmobile.com</a>				
Included Items	CHS barcode scanner, AAA rechargeable batteries (2), USB AC charger kit, lanyard/belt clip with retractable tether, software			CHS barcode scanner, rechargeable battery (pre-installed), USB AC charger kit, Lanyard Software	
Warranty	Scanner: One year Accessories: 90 days				
SocketCare Extended Warranty	Sold separately. SocketCare Plus 2 Year - SKU# SC1804-1349 SocketCare Plus 3 Year - SKU# SC1805-1350 <a href="http://www.socketcare.com/">http://www.socketcare.com/</a>				
Charging Cradle	SKU# AC4055-1382	SKU# AC4056-1383	SKU# AC4055-1382	SKU# AC4055-1382	SKU# AC4056-1383
DC Power Supply (Car Charger)	SKU# AC4057-1384				
Battery Replacement Kit:	SKU# AC4059-1479			SKU# SV3224-1462	
Electrical Safety / Environmental	Certified to IEC 60950-1, UL 60950-1, CAN/CSA C22.2 Environmental: RoHS				
EMI / RFI	FCC Part 15 Class C, RSS 210, ICES 003, C-Tick, CISPR 22, CE EN55022, EN55024, TELEC				
Laser / LED Safety	IEC 60825-1, EN 60825-1				

<sup>1</sup>Temperature ranges may vary with battery shelf life. <sup>2</sup>Battery life may vary with vibrate settings and work environment. <sup>3</sup>Depends on symbol size, symbology, label media, W-N ratio, scan angle.



sales@socketmobile.com

	Worldwide	EMEA
	+1 510 933 3000	+32 479 49 64 54
	Toll-Free	UK
	+1 800 552 3300 (USA/Canada)	+44 7787 112109
		Asia Pacific
		+1 510 933 3122
		Latin America
		+1 510 933 3153