QX Stand

Highly Stylish Hands-Free Mobile Coupon Scanning for Mobile Point of Sale and Hospitality Solutions

Benefits

- **Supports mobile coupons** - Customers can scan their mobile coupons to redeem merchandise or present electronic coupons and tickets by passing their mobile devices under the barcode scanner.

- **Quick release**- The QX Stands' quick release mechanism facilitates a seamless transition between Stand Mode and Mobile Mode.

- **Customers keep control of their devices** - The QX Stand will enable customers to securely scan mobile coupons without relinquishing control of their mobile devices.

- **Charging** - The QX Stand contains contacts designed to match the CHS Series 7 scanners charging pins enabling the scanner to charge & operate under AC power when mounted in the QX Stand. An LED indicates power connection. An AC Adapter with a USB cable is included.

- **Elegant & functional** - The QX Stands' design was carefully chosen to match the CHS Series 7 scanner style of form and function as well as to complement your mPOS solution.

- **Secure mounting** - The QX Stands' robust design is specifically engineered for secure mounting of the CHS scanner. A magnet embedded in the QX Stand guides the CHS Series 7 scanner into alignment and holds it in place.

- **Compatible** - CHS Series 7 Colorful and Durable 2D scanners provide full support for the QX Stand. The QX Stand supports 1D scanners for charging only. Older 2D CHS models can be updated. See Socket Mobile support for CHS upgrade programs.

The QX Stand is an accessory charging stand for the CHS Series 7 7Qi and 7Xi models. The QX Stand provides hands-free scanning (while in the QX Stand) and a quick transition to trigger scanning (when removed from the QX Stand).

Supports Mobile Coupons

- **Stationary with a twist** - The QX Stands docking Arch is mounted using a gimbal & socket to allow a 360 degree rotation and 3D tilt.

- **The scanner knows** - The QX Stands' detection pins lets the scanner know it is mounted on a QX Stand. This facilitates a dynamic user environment when moving the scanner from the QX Stand to the hand. (CHS 7Qi and 7Xi only)

- **Smart SDK** - When mounted atop the docking Arch, the SocketScan SDK can configure the CHS Series 7 scanner for a good scan LED & Beep tone indication; vibrate indication off and Unattended Mode. Then, back again when you and your scanner are on the move.

Hardware Features

Holder:
- Built-in hook and cradle to securely hold the scanner in place
- Magnet ensures proper alignment for charging
- Audible beep (adjustable) provides confirmation when the scanner is properly seated
- Gimbal & Socket with thumb-lock screw enable 360
- rotation and front/back tilt
- Lanyard support included with relocated Lanyard
- connection to the battery door twist-lock

Base:
- Rubber feet and a weighted base prevents sliding
- Magnets to hold the QX Stand on a metal surface
- Keyholes to screw-mount the QX Stand to a surface (optional)

Electrical:
- MicroUSB for connection to AC Adapter (included)
- QX Stand microLED indicates power connection
- Scanner LED indicates when it is fully charged (solid green)

Supported Scanner Models

Hands-free operation and AC Power/Battery Charge:
- Colorful Scanners: 7Qi* - requires QX Stand Colorful CHS Battery Door (AC4084-1581)
- Durable Scanners: 7Xi* - requires QX Stand Durable CHS Battery Door (AC4085-1582)

AC Power/Battery Charge only:
- Colorful Scanners: 7Ci, 7Mi - requires QX Stand Colorful CHS Battery Door (AC4084-1581)
- Durable Scanners: 7Di, 7Pi - requires QX Stand Durable CHS Battery Door (AC4085-1582)

Physical Characteristics

Dimensions:
- Stand Height: 8.75 in (222 mm)
- Holder Width: 1.80 in (46 mm)
- Holder Length: 5.50 in (140 mm)
- Base Diameter: 5.75 in (146 mm)

Total Mass:
- Without Scanner and AC Adapter: 16 oz (454 g)
- With Scanner and without AC Adapter: 17.6 oz (500 g) Antimicrobial Rating:
- JIS Z2801:2000 Test: 2.49 on MRSA 6.07 if cleaned with Sani-Cloth Plus cloth wipes
- Biosafe HM4100, EPA# 83019-1

Included Items
- QX Stand in three pieces (Holder, Base, Stem), minor assembly required
- 1A AC Adapter (international plugs available for EMEA)
- 3m USB Charging Cable

Warranty
90 days

Certifications
- Complies with Part 15, FCC Rules
- RoHS: Directive 2002/9S/EC

* May require firmware update.

Charging Pins and Magnet

Micro USB

Gimbal & Socket

Mounting Hook