

# TSC

The Smarter Choice.

CELEBRATING 20 YEARS



## TA200 SERIES – Desktop Thermal Transfer Bar Code Printer SUPERIOR, AFFORDABLE PERFORMANCE



### KEY FEATURES

- Dual-motor gear driven design
- 102 mm (4") inches per second print speed
- 300 meter (984') ribbon supply on a 25.4 mm (1") core (coated side out)
- 127 mm (5") OD internal media supply, optional external media holder supports 214 mm (8.4") OD label rolls on 76.2 mm (3") core
- Print mechanism for kiosk applications
- 200 MHz 32-bit RISC processor with 8 MB SDRAM, 4 MB Flash memory
- USB 2.0
- Internally scalable true type fonts
- TSPL-EZ™ firmware emulates TPLE and TPLZ languages out of the box
- Free bundled labeling software and Windows drivers
- All TSC printers feature an industry best 2 year limited warranty

### APPLICATIONS

- **Manufacturing & Warehousing**
  - Work in Progress
  - Item Labels
  - Instruction Labels
  - Agency Labels
- **Healthcare**
  - Patient Identification
  - Pharmacy
  - Specimen Identification
- **Parcel Post**
  - Shipping Labels
  - Receiving Labels
- **Small/Home Office**
- **Retail Marking**
  - Price Tags
  - Shelf Labels
  - Jewelry Tags

# TA200 SERIES – Desktop Thermal Transfer Bar Code Printer

PRINTER MODEL	TA200	TA300
Resolution	8 dots/mm (203 DPI)	12 dots/mm (300 DPI)
Printing method	Thermal Transfer & Direct Thermal	
Max. print speed	102 mm (4")/second	76 mm (3")/second
Max. print width	108 mm (4.25")	104 mm (4.09")
Max. print length	2,794 mm (110")	1,016 mm (40")
Enclosure	ABS plastic	
Physical dimension	224 mm (W) x 186 mm (H) x 294 mm (D) 8.82" (W) x 7.32" (H) x 11.57" (D)	
Weight	2.45 kg (5.4 lbs)	
Label roll capacity	127 mm (5") OD	
Ribbon	300 m long, max. OD 67 mm, 1" core (ink coated outside)	
Ribbon width	40 mm ~ 110 mm (1.6" ~ 4.3")	
Processor	32-bit RISC CPU	
Memory	<ul style="list-style-type: none"> <li>• 4 MB Flash memory</li> <li>• 8 MB SDRAM</li> <li>• microSD card reader for Flash memory expansion, up to 4 GB (factory option)</li> </ul>	
Interface	<ul style="list-style-type: none"> <li>• USB 2.0</li> <li>• RS-232 (factory option)</li> <li>• Centronics (factory option)</li> <li>• Internal Ethernet, 10/100 Mbps (factory option)</li> <li>• Bluetooth (user option)</li> <li>• External 802.11 b/g/n wireless (user option)</li> </ul>	
Power	External universal switching power supply <ul style="list-style-type: none"> <li>• Input: AC 100-240V, 1.8A, 50-60Hz</li> <li>• Output: DC 24V, 2.5A, 60W</li> </ul>	
Operation switch, button, LED	1 power switch, 1 feed button & 1 LED (3 colors: green, amber & red)	
Sensors	<ul style="list-style-type: none"> <li>• Transmissive gap sensor (position adjustable)</li> <li>• Black mark reflective sensor (position adjustable)</li> <li>• Ribbon end sensor</li> <li>• Head open sensor</li> </ul>	
Internal fonts	<ul style="list-style-type: none"> <li>• 8 alpha-numeric bitmap fonts</li> <li>• Monotype Image® true type font engine with one CG Triumvirate Bold Condensed scalable font</li> </ul>	
Bar code	<ul style="list-style-type: none"> <li>• 1D bar code Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST, GS1 DataBar, Code 11</li> <li>• 2D bar code PDF-417, Maxicode, DataMatrix, QR code, Aztec, GS1 DataBar Composite Code</li> </ul>	
Font and barcode rotation	0, 90, 180, 270 degree	
Printer language	TSPL-EZ™ (Compatible to EPL, ZPL, ZPL II)	
Media type	Continuous, die-cut, black mark, fan-fold, notched (outside/inside wound)	
Media width	25.4 ~ 118 mm (1.0" ~ 4.6")	
Media thickness	0.06 ~ 0.254 mm (2.36 ~ 10 mil)	
Media core diameter	25.4 ~ 38 mm (1" ~ 1.5")	
Label length	10 ~ 2,794 mm (0.39" ~ 110")	10 ~ 1,016 mm (0.39" ~ 40")
Environment condition	Operation: 5 ~ 40°C, 25 ~ 85% non-condensing Storage: -40 ~ 60°C, 10 ~ 90% non-condensing	
Safety regulation	FCC Class A, CE Class A, CCC	
Environmental concern	Comply with RoHS, WEEE	
Accessories	<ul style="list-style-type: none"> <li>• Windows labeling software CD disk</li> <li>• Quick start guide</li> <li>• USB cable</li> <li>• Power cord</li> <li>• External universal switching power supply</li> <li>• Label spindle, fixing tab x 2</li> <li>• Ribbon spindle x 2</li> <li>• Ribbon paper core</li> </ul>	
Limited warranty	<ul style="list-style-type: none"> <li>• Printer: 2 years</li> <li>• Print head: 25 km (1 million inches) or 12 months which comes first</li> <li>• Platen: 50 km (2 million inches) or 12 months which comes first</li> </ul>	
Factory options	<ul style="list-style-type: none"> <li>• RS-232 serial interface</li> <li>• 128 x 64 pixels graphic type LCD display with back light</li> <li>• Centronics parallel interface</li> <li>• Internal Ethernet interface (10/100 Mbps)</li> <li>• microSD card reader (standard in EMEA)</li> <li>• Real time clock (standard in EMEA)</li> </ul>	
Dealer options	<ul style="list-style-type: none"> <li>• Peel-off module</li> <li>• Guillotine cutter (full cut or partial cut)</li> </ul>	
User options	<ul style="list-style-type: none"> <li>• External roll mount, media OD. 214 mm (8.4") with 76.2 mm (3") core</li> <li>• Bluetooth module (serial interface)</li> <li>• 802.11 b/g/n wireless module (serial interface)</li> <li>• 1.5" core adapter x 2</li> <li>• KP-200 Plus keyboard display unit</li> <li>• KU-007 Plus programmable smart keyboard</li> </ul>	



## CORPORATE HEADQUARTERS

**TSC Auto ID Technology Co., Ltd.**  
 Tel: +886 2 2218 6789  
 E-mail: printer\_sales@tsprinters.com

## LI ZE PLANT

**TSC Auto ID Technology Co., Ltd.**  
 Tel: +886 3 990 6677  
 E-mail: printer\_sales@tsprinters.com

## AMERICAS

**TSC Auto ID Technology America Inc. Corporate Office**  
 Tel: +1 909 525 9779  
 E-mail: sales@tsprinters.com

## Orlando Office

Tel: +1 407 704 8918  
 E-mail: sales@tsprinters.com

## CANADA

**TSC Auto ID Technology America Inc.**  
 Tel: +1 909 525 9779  
 E-mail: sales@tsprinters.com

## MEXICO

**TSC Mexico Representative Office**  
 Tel: +52 (33) 3836 6682  
 E-mail: sales@idc-componentes.com

## BRAZIL

**TSC Brazil Representative Office**  
 Tel: +55 (11) 9597 8098  
 E-mail: sales@tsprinters.com

## EMEA

**TSC Auto ID Technology EMEA GmbH**  
 Tel: +49 (0) 8106 37979 00  
 E-mail: info@tsceu.com

## RUSSIA

**TSC Auto ID Technology EMEA GmbH**  
 Tel: +7 915 422 8889  
 E-mail: info@tsceu.com

## MIDDLE EAST

**TSC Auto ID Technology ME Ltd, FZE**  
 Tel: +971 4 2533 069  
 E-mail: info@tsmea.com

## ASIA PACIFIC

**TSC Auto ID Technology Co., Ltd.**  
 Tel: +886 2 2218 6789  
 E-mail: printer\_sales@tsprinters.com

## CHINA

**Tianjin TSC Auto ID Technology Co., Ltd.**  
 Tel: +86 22 5981 6661  
 E-mail: sale@tsprinters.com.cn

TSC is a trademark of TSC Auto ID Technology Co., Ltd.  
 TSC Auto ID Technology Co., Ltd. is an ISO 9001/14001 registered company.  
 © 2013 TSC Auto ID Technology Co., Ltd.  
 Product models and Specifications are subject to change without notice.  
 Contact your TSC sales representative for specific information.