

HANDS-FREE SCANNER

- Product availability and specifications depend on territory market strategy; all are subjects to change without prior notice.
- ZEBEX is the trademark of ZEBEX INDUSTRIES INC, all rights reserved.



Z-6170

Hands-Free Single-Laser Omnidirectional Scanner

Elegant and functional, the Z-6170 leads the trend to the next aesthetical level. Its distinctive white/black color fits perfectly into places like bookstore, boutique and anywhere delicacy is a must. With unique designed single-laser scan engine, the scanner has 20-line omnidirectional laser beams reading at 1,400 scans per second, and upgraded CPU for decoding most popular 1D barcodes at an unbeatable performance.

- Single-line trigger button
- Tilttable stand with hinge shaft design
- Advance decoding design for fast and accurate scanning
- Unique plastic suction cup for easy field installation
- Honored by **Taiwan Excellence 2010**



OPERATIONAL

Light Source	650 nm visible laser diode (VLD)
Depth of Field	0 – 200 mm (UPC/EAN 100%, PCS=90%)
Scan Pattern	5 directions of scan field
Scan Rate	1,400 scans per second (omnidirectional); 74 scans per second (single-line)
Scan Line	20
Minimum Bar Width	5 mil @ PCS=90%
Print Contrast	30% @ UPC/EAN 100%
Indicator	Two-color LED (blue, red)
Beeper Operation	Programmable tone & volume
System Interface	Keyboard, RS-232, HID USB, USB Virtual COM, OPOS, JPOS

PHYSICAL

Dimension	118.0 × 100.0 × 165.1 mm
Weight	360 g (without cable)
Cable	Standard 2M straight

POWER

Input Voltage	5 VDC ±10%
Power Consumption	1.35 watts
Operating Current	270 mA (typical); 350 mA (peak)

REGULATORY


Laser Class	CDRH Class IIa; IEC 60825-1: Class 2
EMC	CE EN55022 B, FCC Part 15 Class B, VCCI, BSMI

ENVIRONMENTAL

Operating Temperature	0°C – 40°C (32°F – 104°F)
Storage Temperature	-20°C – 60°C (-4°F – 140°F)
Humidity	5% – 90% RH (no dewing allowed)
Light Level	Up to 4,000 Lux (fluorescence)
Drop Durability	Designed to withstand 1M drops

DECODING CAPABILITY

1D Barcode	UPC/EAN/JAN, UPC-A & UPC-E, EAN-8 & EAN-13, JAN-8 & JAN-13, ISBN/ISSN, Code 39, Codabar, Code 128 & EAN 128, Code 93, ITF, Addendum 2 of 5, IATA Code, MSI/Plessey, China Postal Code, Code 32, Industrial 2 of 5, Standard 2 of 5, DTF, JAP, Code 11, RSS 14, RSS Limited, RSS Expanded
------------	--



1. Distinctive indicator & large trigger button
2. Unique suction cup design
3. Hinge shaft for tilting angles
4. Easy field replaceable cable

