

CL-\$700

CITIZEN

Industrial printing with added speed and capacity

High-speed industrial printing

Space-saving design concept

The Hi-Open[™] case lifts up vertically meaning that the printer's footprint does not change as the cover is opened making it ideal for tight spaces.

Optional peeler

An optional peeler can be added to the CL-S700II giving the peel-and-present function without the height of the full liner rewinder case.

Easy configuration

The large graphic LCD gives a clear indication of printer status and easy printer configuration.

CL-S700II

Label, Industrial

Applications

- Healthcare
- Logistic / Transport
- Manufacturing
- Warehousing
- Rental / Hiring



High performance with easy access

TOMORROW'S PRINTING TODAY

Citizen Systems Europe GmbH, Elizabeth House, 56-60 London Road, Staines-Upon-Thames, TW18 4HF, United Kingdom

CITIZEN SYSTEMS EUROPE GMBH

CITIZEN

Specifications

Model	CL-S700II
Printing Technology	Thermal Transfer + Direct Thermal
Resolution	203 dpi
Print Speed (maximum)	10 inches per second (254 mm/s)
Print Width (maximum)	4 inches (104 mm)
Media Width (min to max)	1 to 4 inches (25 to 118 mm)
Roll Size (max), Core Size	Outside diameter 8 inches (200 mm) Core size 1 inch (25mm) Plus Outside media slot
Media Thickness (min to max)	63.5 to 254 μm
Media Length (min to max)	0.25 to 99.99 inches (6.35 to 2539.74mm)
Media Sensor	Fully adjustable rear sensor and high resolution front sensor
Main Interface	Triple interface USB, parallel and serial built-in, exchangeable interface card slot for optional card
Interface	Wireless LAN 802.11b and 802.11g standards, 100 metres, 64/128 bit WEP, WPA, up to 54Mbps, Ethernet (10/100 BaseT)
Ribbon size	3.4 inches (86.5 mm) maximum outside diameter. 450 metres length.
Ribbon winding & type	Ink side in or out, automatically sensing. Wax, Wax/Resin or Resin Type
Ribbon system	ARCP™ automatic ribbon tension adjustment
Mechanism	Hi-Lift™ metal mechanism with wide opening head

CL-S700II

Label, Industrial

Features & Benefits

- Hi-Open[™] case for vertical opening, no increase in footprint and safe closing.
- No more unreadable labels the ARCP[™] ribbon control technology assures clear prints.
- Low space requirement integrated power supply enables clean work station
- ENERGY STAR® compliant
- Recyclable packacking
- Basic peeler



Ingeniously designed for easy operation and reliability

CITIZEN

Model	CL-S700II
Control panel	4 buttons, 4-line back-lit graphic LCD
Emulations (Languages)	Citizen Original Commands, Datamax® I-Class™ & DMX400™, Cross-Emulation™ - automatic switching between Zebra® ZPL-II® and Datamax® I-Class®, DMX400, Zebra® ZPL-II®, BASIC interpreter for data stream processing, EPL-2®
Drivers and software	Free-of-charge on CD with printer, including support for various platforms
Flash (Non-Volatile Memory)	16 MB total, 4MB available for user
Size (W x D x H) and Weight	255 x 490 x 265 mm, 13.3 Kg
Warranty	2 years on printer. 6 months or 50 Kms printhead

All product names are trademarks of the respective manufacturers. Zebra®, ZPL and EPL are trademarks of ZIH Corp. Datamax® is a trademark of Datamax. O'Neil Corporation. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded. © Citizen Systems Europe GmbH, V.1.0

CL-S700II

Label, Industrial