



Table Charger System for PDA 2, 4, 6 and 8-Slot solutions

Technical Information

General Information

Table charger size	2-Slot	4-Slot	6-Slot	8-Slot
Length:	90 mm	165 mm	240 mm	310 mm
Width:	125 mm	125 mm	125 mm	125 mm
Height:	55 mm	55 mm	55 mm	55 mm

Charger Slots

Input power:	12V2A	12V5A	12V5A	12V5A
Output power per slot:	5VDC2.1A	5VDC2.1A	5VDC2.1A	5VDC2.1A
Charging time:	Normally 1-4 hours, PDA Dependant			
Warranty:	1-years, Option 2-5 years			
Approval:	CE / RoHs / US FCC			



Order Information

For device	2-Slot	4-Slot	6-Slot	8-Slot
ZEBRA TC20	5240-239X	5440-239X	5640-239X	5840-239X
ZEBRA TC51/56 BOOT	5240-219X	5440-219X	5640-219X	5840-219X
ZEBRA TC51/56 NoBOOT	5240-229X	5440-229X	5640-229X	5840-229X
Honeywell EDA50	5250-159X	5450-159X	5650-159X	5850-159X
Honeywell EDA50K	TBD	TBD	TBD	TBD
Honeywell CT40 BOOT	5250-169X	5450-169X	5650-169X	5850-169X
Honeywell CT40 NoBOOT	5250-179X	5450-179X	5650-179X	5850-179X
Honeywell CT50/60	5250-149X	5450-149X	5650-149X	5850-149X
Samsung Xcover 3*	5200-109X	5400-109X	5600-109X	5800-109X
Samsung Xcover 4*	5200-119X	5400-119X	5600-119X	5800-119X

PSU Adapter

(X=90 incl. PSU Adapter, X=91 excl. PSU Adapter.

PSU Wall Adapter EU Plug Only 12V2A	160-005-123	-	-	-
PSU Adapter EU/UK/US (C6) 12V5A Order Powercord separatly!	160-005-125	160-005-125	160-005-125	160-005-125

Powercord for PSU ADAPTER (160-005-125) IEC60320 C5 (Power Cord is not included, order separatly)

Power cord 1,5m EU Plug	160-005-EU	160-005-EU	160-005-EU	160-005-EU
Power cord 1,5m UK Plug	160-005-UK	160-005-UK	160-005-UK	160-005-UK
Power cord 1,5m US Plug	160-005-US	160-005-US	160-005-US	160-005-US

Cradle of Sweden develops and manufactures products and solutions for stationary and vehicle mounted charging of PDAs, as well as solutions for communication between PDAs, vehicles and surroundings within complex mobile data systems.

