DLQ-3500II

DATASHEET / BROCHURE





Premium, multi-part dot matrix device - print one original and up to seven carbon copies. This low energy unit features an LCD screen

Ideal for logistics and warehousing businesses, along with government and public sector organisations, the DLQ-3500II is a premium, efficient dot matrix printer, with an LCD screen, that's exceptionally economical to run and is ultrareliable across all stationery types

In challenging printing conditions, the robust DLQ-3500II 24-pin dot matrix printer provides premium performance, allied to reduced energy use. With sturdy casing and reliable dot matrix technology, it's capable of delivering high-quality output even when the environment is dusty or active.

Equally, when time is tight, the DLQ-3500II delivers fast printing of up to 550 characters per second (High-Speed-Draft, 10cpi), via a fast and robust 24-pin dot matrix printer with 136 columns.

The printer's performance is matched by its cost-effectiveness. Thanks to the efficient and reliable dot matrix technology, and low-cost ribbons, it represents a printing solution that is extremely budget friendly.

An LCD screen also provides valuable user convenience.

The only 24-pin dot matrix printer on the market with 8 prints in one.1

KEY FEATURES

Versatile

Prints multiple forms (one original and up to seven copies)

• Fast performance

Prints up to 550 characters per second with up to 7 copies

• Minimal intervention

Automatic paper path change and automatic paper-strength settings

• Ease of use

Featuring a new LCD screen

• Flexible connectivity

Parallel and USB ports



PRODUCT SPECIFICATIONS

TECHNOLOGY

Number of Pins 24 pins Number of columns 136 columns

PRINT

Printing Speed Draft: 10 cpi: 550 chars/s, HighSpeed-Draft: 10 cpi: 550 chars/s, LQ: 10 cpi: 195 chars/s Code 128, Code 39, EAN-13, EAN-8, Interleaved 2 of 5, POSTNET, UPC-A, UPC-E Barcodes

Carbon Copies 7 plus one original

PCAPTEC, PC437, PC720, PC850, PC858, PC864, PCAR864, ISO-8859-1, ISO-8859-15, **Character Tables**

Roman 8. Italic

PAPER / MEDIA HANDLING

Document Feed Single sheet front and rear, Continuous media front and rear, Paper output front, bulk

measurement: yes

Paper Formats Sheet Paper (single- and multi-layer), Continuous Paper (single- and multi-layer), Envelopes,

Cardboard

Paper Thickness Continuous 0.12 mm - 0.62 mm

Paper Thickness Label Total 0.16 mm - 0.19 mm

Paper Thickness Multi Part 0.12 mm - 0.62 mm Paper Thickness Single Sheet 0.065 mm - 0.19 mm

GENERAL

Power consumption 78 Watt, 0.8 Watt (standby) Supply Voltage AC 100 V - 240 V, 50 Hz - 60 Hz

661 x 433 x 276 mm (Width x Depth x Height) Product dimensions

Product weight

Operation 5° C - 35° C Supported Temperature

Compatible Operating Windows 10, Windows 7, Windows 8, Windows XP

Systems

Included Software **Epson Status Monitor** Mean Time Between Failures 10,000 hours

200 Million Strokes/Wire Print Head Life Noise Operation: 59 dB (A) 128 MB Included Memory

Ribbon Yield 9000000 characters Black Draft

Operation 10% - 80% Supported Humidity

OTHER FEATURES

Input Data Buffer 128 kB

OTHER

Warranty 12 months On-site service

Optional warranty extension available

LOGISTICS INFORMATION

SKU	C11CH59402
EAN code	8715946668185
Country of Origin	Indonesia

DLQ-3500II

SUPPLIES

- Epson SIDM Black Ribbon Cartridge for DLQ-3000/+/3500 (C13S015139) (C13S015139)
- Epson SIDM Black Ribbon Cartridge for DLQ-3000/+/3500 (C13S015066) (C13S015066)

1. ¹The DLQ-3500II is the only product on the market to product an original and seven copies. Checked against competitor products as of October 2019.



www.epson.co.uk

www.epson.ie