BADGY100 TECHNICAL FEATURES

badgy A LASTING IMPRESSION



SOFTWARE

- Supplied with: Evolis Badge Studio[®] (Standard version)
- Compatible with Windows[®] and Mac

PACKAGE CONTENTS

- BADGY100 printer
- Color ribbon (YMCKO) 50 prints
- 50 blank PVC cards 0.76 mm (30 mil)
- Installation CD including print driver, card templates, Evolis Badge Studio[®] software (Standard version)
- Power supply unit and cable
- USB cable

DIMENSIONS AND WEIGHT

- Complete packaged solution:
 Dimensions (H x W x D): 315 x 385 x 285 mm (12.4" x 15.15" x 11.22")
 Weight: 3.95 kg (8.7 lbs)
- Printer:
 Dimensions (H x W x D): 148 x 200 x 276 mm (5.83" x 7.87" x 10.87")
 - Weight: 1.665 kg (3.67 lbs)

WARRANTY CONDITIONS¹

- 1 year (printer and print head)
- Warranty extensions available as an option

- GENERAL FEATURES
- Single-side print module
- Color sublimation, monochrome thermal transfer
- Printing resolution: 260 x 300 dpi
- 2 million colors
- 16 MB of memory (RAM)
- Printable area: margin of 1.35 mm

PRINTING SPEED

- Color (YMCKO): 45 sec/card 80 cards/hour
- Black: 16 sec/card 225 cards/hour

PORTS/CONNECTIVITY

USB 2.0 (USB 1.1 and 3.0 compatible)

SECURITY

Space for Kensington[®] security lock

ECO-DESIGN, CERTIFICATIONS AND DECLARATION OF CONFORMITY

- Extended standby mode and reduced electricity consumption
- CE, FCC, VCCI, BIS, CCC, KC
- RoHS

POWER SUPPLY

- Power supply unit: 100-240 V AC, 50-60 Hz, 1.7 A
- Printer: 24 Volts DC, 2.71 A

MANAGEMENT AND CARD FEATURES

- Card feeder capacity: 25 cards (0.76 mm) to 40 cards (0.50 mm)
- Output hopper capacity: 25 cards (0.76 mm) to 40 cards (0.50 mm)
- Card thickness: 0.50 to 0.76 mm, automatic adjustment of the gauge
- Card type: PVC cards
- Card format: ISO CR-80 ISO 7810 (53.98 x 85.60 mm)
- Included in the solution: pack of 50 PVC cards 0.76 mm

PRINTING RIBBONS

- Included in the solution:
- YMCKO: 50 prints/ribbon
- Available to order:
- YMCKO: 100 prints/ribbon • Monochrome black ribbon:
- 500 prints/ribbon (integrated ribbon saving)
- Automatic recognition and configuration
- Ribbon inserted in a cassette for easier handling

OPERATING SYSTEMS

- Windows[®] XP, Vista 32/64, W7 32/64, W8 32/64, W10 32/64
- Mac OS X 10.6, 10.7, 10.8, 10.9

OPERATING ENVIRONMENT

- Min/max operating temperature: 15° / 30° C (59° / 86° F)
- Humidity: 20% to 65% non-condensing
 Min/max storage temperature:
- -5° / +70° C (23° / 158° F)
- Storage humidity: 20% to 70% non-condensing
- Ventilation in operation: free air circulation

1 Warranty subject to strict compliance with the specific usage conditions and the use of Badgy print ribbons. The costs of return remain the responsibility of customer.