



B360 FULLY RUGGED NOTEBOOK

- MIL-STD 810H, 6 foot drop rating, IP66 certified, and optional salt fog resistant
- 10th Generation Intel® Core™ Processor
- 13.3" FHD LumiBond® 2.0 Display with Getac Sunlight Readable Technology (1,400 nits) and Capacitive Touchscreen
- Enhanced Enterprise Security with optional dual user replaceable storage, Windows Hello Face-authentication Camera, integrated 1D / 2D Imager Barcode Reader and Multi-factor Authentication Options
- LifeSupport[™] Battery SwappableTechnology















Specifications

Generation

Operating System

Windows 10 Pro

Mobile Computing Platform

Platform Options:

Intel® Core™ i7 Technology Intel® Core™ i7-10510U Processor 1.8 GHz Max. 4.9 GHz with Intel® Turbo Boost Technology

- 8MB Intel® Smart Cache

Intel® Core™ i7 Technology
Intel® Core™ i7-10710U Processor 1.1 GHz
Max. 4.7 GHz with Intel® Turbo Boost Technology
- 12MB Intel® Smart Cache

Intel® Core™ i5 Technology Intel® Core™ i5-10210U Processor 1.6 GHz Max. 4.2 GHz with Intel® Turbo Boost Technology - 6MB Intel® Smart Cache

VGA Controller

Intel® UHD Graphics

13.3" IPS TFT LCD FHD (1920 x 1080) 1400 nits LumiBond® display with Getac sunlight readable technology

Capacitive multi-touch screen

Storage & Memory
Optional 8GB / 16GB / 32GB / 64GB DDR4
Optional main storage: 256GB / 512GB / 1TB PCIe NVMe SSD Optional 2nd storageⁱ: 256GB / 512GB / 1TB SATA SSD

Keyboard

LED backlit membrane keyboard Optional LED backlit rubber keyboard

Pointing Device

Touchscreen

Capacitive multi-touch screen

Touchpad
- Glide touchpad with multi-touch

Expansion Slot

Smart Card reader x 1 SD Card reader x 1 Optional 1D / 2D imager barcode reader

I/O Interface

FHD webcam x 1 or Optional Windows Hello face-authentication camera (front-facing) x 1 Headphone out/mic-in Combo x 1 DC in Jack x 1 USB 3.1 Gen 2 Type-A x 2 PowerShare USB 2.0 x 1 LAN (RJ45) x 1

HDMl x 1 Docking connector x 1

Optional SIIM card slot x 1
Optional SIIM card slot x 1
Optional RF antenna pass-through for GPS,
WLAN and WWAN

Configurable I/O Options⁸: Serial port (9-pin; D-sub) x 1 + External VGA (15-pin; D-sub) x 1, or Serial port (9-pin; D-sub) x 1 + USB 3.1 Gen 2 Type C x 1, or

Serial port (9-pin; D-sub) x 1 + Display Port x 1

Communication Interface

10 / 100 / 1000 base-T Ethernet Intel® Wi-Fi 6 AX200, 802.11ax
Bluetooth (v5.1)^{III}
Optional dedicated GPS^{IV}
Optional 4G LTE mobile broadband with integrated GPS^{IV}

Security Feature

TPM 2.0

Smart Card reader x 1 Kensington lock Optional HF RFID Reader

AC adapter (90W, 100-240VAC, 50 / 60Hz) Li-lon battery (11.1V, typical 2100mAh; min. 2040mAh) x 2

LifeSupport[™] battery swappable technology

Dimension (W x D x H) & Weight 342 x 281 x 34.9 mm (13.46" x 11.06" x 1.37"), 2.32 kg (5.11 lbs)"

Rugged Feature

MIL-STD-810H certified and IP66 certified MIL-STD-461G certified Optional ANSI/UL 121201, CSA C22.2 NO. 213 6 feet drop resistant^{viii} Optional salt fog certified e-Mark certified for vehicle usage

Environmental Specification

Temperature^{vii}

- Operating: -29°C to 63°C / -20°F to 145°F Storage: -51°C to 71°C / -60°F to 160°F
- Humidity: 95% RH , non-condensing

Software

Getac Utility Getac Geolocation Getac Barcode Manager Optional Absolute DDS® Persistence

Accessories

Backnack Multi-bay charger (Dual Bay)

Multi-Bay charger (Eight-Bay)

Vehicle adapter (120W, 11-32VDC)

MIL-STD-461 certified AC adapter (90W, 100-240VAC)

Capacitive stylus (Hard-tip)

Protection film

Standard battery (11.1V, typical 2100mAh; min. 2040mAh)

AC adapter (90W, 100-240VAC) AC adapter for office dock (120W, 100-240VAC) Spare SSD kit

Office dock

Bumper-to-Bumper warranty

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment

That is why Getac has introduced accidental damage as standard under our new Bumper-to-Bumper warranty, to help minimize your enterprise IT costs.

Bumper-to-Bumper is your hassle-free guarantee. That means you can depend on us to have your unit back in service within days.

Standard

3 years Bumper-to-Bumper

- Second storage is optional and will be fitted with a removable cover when not chosen at
- with a removable cover when not chosen at point of purchase.

 ii External VGA, USB 3.1 Gen 2 Type C and Display Port are mutually exclusive.

 iii Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.

 iv Dedicated GPS is mutually exclusive with 4G LTE mobile broadband.
- LTE mobile broadband. HF(13.56MHz) Combo HF RFID/NFC reader
- (iClass, HID Prox compliant, ISO 15693, 14443
 AB, Mifare, Felica").
 vi Weight and dimensions vary from configurations and optional accessories.
 vii MIL-STD-461G 90W AC adapter sold

- separately.

 viii Tested by a national independent third party test lab following MIL-STD-810H.

Fully Rugged Notebook



Docking Solutions

	Vehicle Dock	Office Dock
Serial Port	1	1
External VGA	1	1
Microphone		1
Audio Output		1
DC in Jack	1	1
USB	6	5
LAN	2	2
HDMI	1	1
RF Antenna Connector	(GPS, WWAN, WLAN) (optional)	
Kensington Lock	1	1

Getac

Getac (UK) Ltd.

Getac House, Stafford Park 12, Telford, Shropshire TF3 3BJ, United Kingdom Tel: +44 (0) 1952 207 222 Sales-Getac-UK@getac.com | www.getac.com/en/



Copyright @ 2020 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved available specification shall be subjected to quotation by request. V01M05Y20UK