

Getac

Rugged Mobile Computing Solutions

T800-Ex Fully Rugged Tablet



- ATEX & IECEx Explosive Atmosphere Certified
- 8.1" HD LumiBond® display for better viewing experience
- Getac proprietary SnapBack add-on featuring 2nd expanded battery
- Optional 1D/2D imager barcode reader
- LifeSupport™ battery swappable technology for uninterrupted battery life
- MIL-STD-810G and IP65 certified



SnapBack Add-on



T800-Ex Fully Rugged 8.1" Tablet

Getac recommends Windows.



Specifications

Operating System	Windows 10 Professional	Software	Getac Utility (including Power Management) Getac Geolocation Getac Barcode Manager Adobe® Reader® Optional Absolute DDS® Persistence
Mobile Computing Platform	Intel® Atom Processor x7-Z78700 1.6GHz, burst up to 2.40 GHz - 2MB Cache	Security Features	TPM 2.0
VGA Controller	Intel® HD Graphics	Power	AC adapter (65W, 100-240VAC, 50 / 60Hz) Li-Ion battery (7.4V, 4200mAh) (up to 8 hours of battery life) ⁱ LifeSupport™ battery swappable technology (only with SnapBack 2nd expanded battery)
Display	8.1" IPS TFT LCD HD (1280 x 800) 600 nits LumiBond® display with Getac sunlight readable technology	Dimension (W x D x H) & Weight	227 x 151 x 24 mm (8.93" x 5.94" x 0.94") 0.91kg (2 lbs) ⁱⁱ
Storage & Memory	4GB LPDDR3 expandable to 8GB eMMC 64GB / 128GB	Rugged Features	MIL-STD-810G certified and IP65 certified 6 feet drop resistant Vibration & drop resistant
Keyboard	6 tablet buttons (Windows, Power, Function Key, Camera Capture/ Barcode Reader Trigger, Volume Up, Volume Down)	Environmental Specifications	Temperature ⁱⁱⁱ : - Operating: -21°C to 50°C / -5.8°F to 122°F - Storage: -51°C to 71°C / -60°F to 160°F Humidity: - 95% RH, non-condensing
Pointing Device	Touchscreen - Capacitive multi-touch screen - Optional dual mode touchscreen (multi-touch and digitizer)	ATEX Certifications	ATEX / IECEx zone 2/22 II 3G Ex ic IIC T4 Gc II 3D Ex ic IIIB T130°C Dc
Expansion Slots	Optional 1D/2D imager barcoder reader Optional SnapBack add-on: 2 nd expanded battery ⁱ	Accessories	Main battery (7.4V, 4200mAh) 2nd expanded battery (14.4V, 2100 mAh) AC adapter (65W, 100-240VAC) Capacitive stylus (Hard-tip) Digitizer pen
I/O Interface	FHD webcam x1 8M pixels auto focus rear camera x1 USB 3.0 (9-pin) x1 Headphone out/ Mic-in Combo x1 DC in Jack x1 Micro HDMI x1		
Communication Interface	Intel® Dual Band Wireless-AC 7265, 802.11ac Bluetooth (v4.0) Optional dedicated GPS Optional 4G LTE mobile broadband		

i. Battery life testing conducted under MobileMark 2007. Battery performance will vary upon software applications, wireless settings, power management settings, LCD brightness, customized modules and environmental conditions. The battery has a limited number of charge cycles and may eventually need to be replaced by a Getac service provider. Battery life and charge cycles vary by use and settings.

ii. Weight varies from configurations and optional accessories.

iii. Tested by a national independent third party test lab following MIL-STD-810G.

Getac



Getac UK Limited
Mitac House, Nedge Hill, Telford,
Shropshire, TF3 3AH, U.K.
Tel: +44 1952 207 200
Email: sales-getac-UK@getac.com
www.getac.co.uk

Copyright © 2015 Getac Technology Corporation and/or any of its affiliates. All rights reserved.
All specifications are subject to change without notice. V01M07Y15UK