# **HANN**spree

## **HO 320 HTB 32" Open Frame Touch Monitor**

### Experts in **Display**

### **Open Frame Touch Monitor HO 320 HTB**

31.5" / 80cm Diagonal LED Backlight – Format 16:9

- 1920 x 1080 Full HD 1080P Resolution
- 10-Point Touch P-Cap Technology
- 178° / 178° Ultra Wide Viewing Angle
- 1400:1 High Contrast Ratio
- Video Input: HDMI + VGA
- IP54 (front) Rating Level
- Display Protection: Thickness 4mm
- Multiple Mounting Options
- ≥6H Toughened Hard Panel Surface
- Slim Profile with Narrow Edges







31.5" / 80 cm

Part. No..: HO 320 HTB

#### SIZE, RESOLUTION



16:9 Aspect Ratio



**HDMI VGA** 

CONNECTIVITY, IP LEVEL



178 Ultra-Wide Viewing Angle

VIEWING ANGLE, TOUCH



LOW POWER

Low Power Consumption

OTHER FEATURES



Full HD 1920 x 1080



IP 54 Water & Dust Protection



10 Point Touch



30.000 Hours Lifetime



## HO 320 HTB 32" Open Frame Touch Monitor

### Experts in **Display**

Display Size	80 cm / 31.5" Diagonal
Panel Type	TFT – LED Backlight
Aspect Ratio	16:9
Resolution (H x V)	1920 x 1080 Full HD
Brightness (Typ.)	350cd/m² Panel / 300 cd/m² Monitor
Contrast (Typ.)	1.400:1 (Typical)
Display Area	698,4 x 392,85 mm
Viewing Angle L/R; U/D	178° H / 178° V
Response Time	8 msec
Pixel Pitch	0,364 (H) x 0,364 (V) mm
Touch Type	Projected Capacitive Type – 10 Point Touch Material Glass + Glass
Display Colors	16.7M Colors
Horizontal Frequency	30 ~ 83 kHz
Vertical Frequency	60 Hz
Max Display Frequency	1920 x 1080 @ 60Hz
Input 1	VGA
Input 2	HDMI
Input 3	USB Type B (Touch)
Input 4	-
Power Consumption	On: 45W; Stand-by: ≤1.2W; Off: ≤1,2W (TBC)
AC Power Range	AC 100 ~ 240 Volt; 50 ~ 60 Hz
Product Dimensions	766 x 54 x 459 mm (W x D x H)
Packing Dimensions	85 x 24.8 x 57 mm (W x D x H) 2 units for each master box
Net / Gross Weight	14 Kg / 31 Kg (gross weight is for 2 units)

VESA Mounting	-
Display Protection	Thickness 4±0.3 mm
Hardness / Transmittance	≥6H Toughened hard panel surface / ≥85%
IP Rating Level	IP 54 (Front), Water and Dust Protection *
Controls	Power, Auto, (+), (-), Menu
LED Backlight life	30.000 hours
Accessory	Power supply; VGA Cable (1.5m); USB Cable for Touch.
Certifications	CE, RoHS
On Screen Display	9 Languages

PART. NO.: HO 320 HTB





<sup>© 2018</sup> HANNSpree, Inc. Specifications and design as well as accessories are subject to change without notice. Screen shots are simulated. Actual products may differ slightly from those illustrated on this promotion material. Please refer to actual samples for final selection. The products displayed on this promotion material may not be available for purchase in your particular country or locality. Please check with your local HANNspree authorized representatives for the availability of specific products in your area. All brand, product, Service names and logos are trademarks and/or registered trademarks of their respective manufactures and Companies.



## HO 320 HTB 32" Open Frame Touch Monitor

## Experts in **Display**

