

Maximum Performance at an Affordable Price

Janam's XT30 is one of the industry's most affordable rugged touch computers and offers mobile professionals the features and functionality needed to reliably run line-of-business applications. Sleek but tough, the XT30 is lightweight and packed with the latest enterprise-grade technologies, delivering maximum performance in a rugged device the fits perfectly in your hand. Designed for small- and medium-sized businesses in the retail, field service, transportation and logistics and warehousing industries, the high-performance XT30 enables organizations to improve mobile applications like asset management, inventory control, price markdown, package tracking and home delivery.

Winning Features:

- Compact and light less than 10 ounces
- Android 9 (GMS or AOSP)
- Brilliant 5-inch touch screen with Gorilla Glass 3
- 2.2 GHz Snapdragon octa-core processor
- Integrated 1D/2D barcode scanning
- RFID and NFC reading capabilities
- 4G LTE, Wi-Fi and Bluetooth
- 4500mAh rechargeable and removable battery













Offering the familiarity of a smartphone, the XT30 is powered by Android 9 (Pie), harnessing the power of machine learning to enhance applications and deliver a powerful user experience. The XT30 with Android 9 automatically adjusts settings based on mobile worker usage, extends battery life and provides the advanced security features enterprises require.



The XT30's brilliant 5-inch display is optimized for use indoors and outdoors and can be used while wearing gloves or when the screen is wet. Integrated 1D/2D scanning, RFID/NFC reading capabilities and front- and rear-facing cameras ensure the XT30 meets virtually all data capture needs, while LPDDR3 memory delivers higher processing speeds and extended battery life up to 12 hours. With an IP65 sealing rating, the XT30 withstands splashes, spills and exposure to rain and survives 5-foot drops to concrete across a wide temperature range.



XT30 Specifications

| TECHNICAL | |
|------------------|--|
| Operating System | Android 9 (Pie) GMS or AOSP |
| Processor | 2.2 GHz Qualcomm Snapdragon™ 660 octa-core |
| Memory | 4GB LPDDR3 RAM/64GB eMMC Flash |
| Expansion | User-accessible microSD card slot with SD and SDHC support |
| Power | 4500mAh rechargeable Li-ion battery |

PHYSICAL

ENVIRONMENTAL

Storage Temperature

Humidity

Water & Dust

Drop

Operating Temperature

Electro Static Discharge (ESD)

| Dimension | 6.0" L x 3.0" W x .7" D / 152mm L x 76mm W x 18mm D |
|-------------|--|
| Weight | 9.8oz / 280g including battery |
| Display | 5.0" High Definition (720x1280) TFT-LCD with Corning® Gorilla® Glass 3 |
| Touch Panel | Capacitive touch screen |

14° to 122° F / -10° to 50° C

-4º to 158º F / -20º to 70º C

+/- 15kV air; +/- 8kV contact

Multiple 5ft / 1.5m drops to concrete on

all sides across a wide temperature range

Non-condensing, 95%

RFID/NFC Reads ISO14443 Type A; ISO14443 Type B; ISO15693; NFC on the 13.56 MHz range Camera 8.0MP color rear-facing autofocus camera with user-controllable LED flash and 2.0MP front-facing camera **NETWORK COMMUNICATION** USB USB 2.0 microUSB TD-LTE: B34/38/39/40/41 WWAN FDD-LTE: B1/2/3/4/5/7/8/12/17/19/20/25/26/ 28A/28B/B66 WCDMA: B1/2/4/5/8 TD-SCDMA: B34/39 GSM/EDGE/GPRS: 850/900/1800/1900 CDMA 2000 EVDO/CDMA 1x (800Mhz) WLAN 802.11a/b/g/n/ac/d/e/h/i/k/r/v/w 802.11.x (EAP): EAP-TLS, EAP-TTLS, PEAP Security MSCHAPv2, PEAP-GTC, PWD, SIM, AKA, WEP, WPA/ WPA-2-PSK, WAPI, WAPI-PSK WPAN Bluetooth v4.1 + BR/EDR + BLE GPS GPS; A-GPS; Bei-Dou satellite navigation ACCESSORIES

Honeywell N6603 1D/2D imager

Single-Slot USB / Charging Cradle Kit

Charging Adapter

DATA CAPTURE

Imager

| SAFETY / REGULATORY | |
|---------------------|-------------------------------------|
| Safety | IEC 60950; EMC; RF; SAR; LED; Laser |
| Radio | FCC; IC; CE |
| Environmental | RoHS and WEEE compliant |

| INTERFACE FEATURES | |
|--------------------|---|
| Audio | 3.5mm headset jack; speaker; microphone |
| Alerts | Vibration; LED indicators |
| LED Indicators | Dual-color |
| External Buttons | Side scan triggers; Volume up/down; Power button; Function key |
| Motion Sensor | Accelerometer; Light Sensor; Proximity Sensor |

IP65



Janam Technologies 100 Crossways Park West Suite 105 Woodbury, NY 11797 Phone: +1.877.JANAM.99 Local: +1.516.677.9500 Fax: +1.516.320.8031 Email: inquiries@janam.com. **Contact Technical Support:** NA: +1.866.915.5311 EMEA: +44.1202.946945 Email: janamcare@janam.com

©2019 Janam Technologies and/or its affiliates. All rights reserved. Janam and the Janam logo are trademarks of Janam Technologies, LLC. All other trademarks are the property of their respective owners.