

METAPACE

Metapace L-42T - Thermal transfer label printer

www.metapace.com

Highlights

- Thermal transfer printer for professional label applications
- Fast printing: up to 178 mm per second
- Particularly large ribbon supply (up to 300 m)
- Standard serial, parallel and USB interfaces
- Complete package: power supply, label roll, transfer tape, software, and cleaning pen included

Technical specifications

Print

Printing method	Direct thermal/Thermal transfer
Print width	max. 108 mm
Print length	6 – 1000 mm
Print speed	max. 178 mm/sec.
Resolution	8 dots/mm (203 dpi) / 12 dots/mm (300 dpi) (optional)

Media

Media type	Gap, Black Mark, Notch, Continuous, Fan-Fold
Media Width	25 – 116 mm
Roll diameter	max. 130 mm
Core diameter	25.4 – 38.1 mm
Media strength	0.06 – 0.2 mm

Ribbon

Ribbon width	33 – 110 mm
Ribbon length	74 m / 300 m
Core diameter	12.5 mm / 25.4 mm

Electronics

Memory	Flash: 128 MB, RAM: 64 MB DDR2
Interfaces	USB 2.0, Serial, Parallel, Ethernet (option), WiFi (option)
Power supply	AC 100V – 240V, DC 24V, 2,5A
Barcodes	All Standard 1D and 2D Barcodes
Reliability	MCBF: min. 12 months; Auto-Cutter: min. 6 months; TPH: min. 6 months

Software

Emulation	EPL, EPL II, ZPL, ZPL II, SLCS
Drivers	Windows 2000, XP (32/64 Bit), 2003 Server (32/64 Bit), Vista (32/64 Bit), Windows 7 (32/64 Bit), Linux (v. 2.4.8 or above), Mac OS (v. 10.4 or above)
Labeldesigner	Metapace Label Designer Software

Specifics

Options	Auto-Cutter, Dispenser, Ethernet, WiFi, external media holder
---------	---

Warranty

Period	24 months
--------	-----------

Housing

Dimension (WxHxD)	214 × 310 × 195 mm
Weight	2.85 kg

**UNPACK &
GET STARTED**
Triple Interface Integrated

LABEL
SOFTWARE
INCLUDED



Drivers
by Seagull™

L-42T
METAPACE