

METAPACE

Metapace S-62 – Competitively Priced Imager

www.metapace.com

Highlights

- Multi-faceted 2D area imager at a great price
- Captures all common 1D, 2D, postal and stacked codes
- Versatile: handheld and presentation modes
- Scan confirmation via green LED and beeper
- Simple connection via USB

Technical specifications

Scanner properties

Type	2D imager
Light source	Lighting: white LED; aiming: red LED, 617 nm
Movement tolerance	100 mm/s, 13 mils UPC
Print contrast	Min. 35 % reflectance difference
Scanning angle	Rotation: $\pm 180^\circ$; pitch: $\pm 65^\circ$; skew: $\pm 60^\circ$
Supported barcodes	Standard 1D and 2D codes

Electronics

Laser rating	EN class B; IEC62471
Voltage	5 V \pm 5 % @ 400 mA

Interfaces

I/F ports	USB
-----------	-----

Specifics

Impact resistance	Resists multiple 1 m drops to concrete
Protection rating	IP40

Environment

Operating temperature	0 °C to 40 °C
Storage temperature	-40 °C to 60 °C
Humidity	5 % to 95 % RH (non-condensing)

Housing

Dimensions (WxHxD)	95 x 68 x 152 mm
Weight	125 g (without cable)
Colour	Black

Warranty

Period	60 month
--------	----------

