

## **DS-650P-P1**

### 65" PCAP Touch Monitor







#### **Description**

Introducing the DS-650P-PI Multi-Touch Display. This display offers a smartphone-like touch experience in a commercial display specially engineered for 24/7 operation. With features like high-performance projected capacitive multi-touch technology, a sophisticated bezel-free design for a truly uncompromised touch experience, an active thermal management system to ensure cool-to-the-touch performance in all display orientations and 4K 3820 x 2160 resolution, this display delivers a premium interactive experience to teach, inspire, inform, and sell.

#### **Featured Specifications**

• Size: 65" TFT LCD

• Maximum Resolution: 3840 x 2160

• Contrast Ratio: 1200:1

· Aspect Ratio: 16:9

Brightness: 450 nits (w/o Touch),
390 nits (P-CAP)

View Angle: H: 178°, V: 178°

 Video Port: HDMI, DVI, VGA, Display Port (HDCP)

• Warranty: 3 year

# **Specifications**

Touch Screen	Projected Capacitive
Touch Points	80 with Palm Rejection   10ms response (up to 20 touches)
Touch Screen Interface	USB
Screen Treatment	Anti-Glare
I/O Ports	
Serial Port	_
USB Port	1 x USB 2.0 (Type B) for Touch Interface (USB-HID)
Video Port	HDMI, DVI, VGA, Display Port (HDCP)
Audio	Audio Input, 5W + 5W @ 8Ω
Power Input	Internal, 110/220 VAC
Physical Properties	
Housing Color	Black
Dimensions (W x H x D) mm	1527.98 x 902.86 x 75.50
Net Weight (kg)	55.5
Gross Weight (kg)	68
Carton (W x H x D) mm	1720 x 1090 x 250
VESA	400×400
Safety	
Certifications	FCC-B, CE, cTUVus, RCM, PSE, CB, CCC
EU Energy Efficiency Class	В
Environment	
Operating Temperature	0° C ~ 40° C, 20% ~ 85% RH. Non-Condensing
Storage Temperature	-10° C ~ 60° C, 20% ~ 85% RH. Non-Condensing
Optional Peripheral	

