

# NORDIC ID SAMPO S1

## NORDIC ID SAMPO S1

Nordic ID Sampo S1 is a fixed UHF RFID reader with an integrated antenna, which come with a flat design.

Nordic ID Sampo S1 is a basic but powerful RFID reader and writer with USB interface for communication and power.



<b>((•))</b>	

**UHF RFID** 

**UHF RFID** 

Frequency band

Regulatory

Supported standard

Typical reading speed

RFID radiated power

Integrated antenna features

USER INTERFACE

Signals and indicators

CONNECTIVITY

External Power Supply

SIZE AND WEIGHT

**ENVIRONMENT** 

Storage Temperature

Environmental sealing

Operating Temperature

Operating Power

Dimensions

Weight

USB

POWER

External antenna port (optional)







AES authentication in accordance with ISO/IEC 29167-10 supported ETSI 865.6-867.6 MHz or FCC/IC 902-928 MHz

External antenna ports (optional): +27dBm (500 mW)

LEDs: Power, RFID on, RFID read and Communication

Light sensor and tapping sensor for triggering reading

Bus powered USB 2.0 device (appears as a serial port)

(W) 200 x (L) 260 x (H) 25 mm ((W) 7.9 x (L) 10.2 x (H) 1.0 inch)

8 dBic circular polarized, Beam width: 80°

Nominal reading distance: 5 m (16 ft)

CE ETSI EN 302 208, CE ETSI EN 301 489, FCC part 15.247 IC RSS-210,

ISO 18000-63 (EPC Class 1 Gen2v2)

Safety IEC 62368-1:2019 ed. 3 200 tags / sec in DRM mode

Adjustable in 1 dB steps

3 pcs. 50 Ω / SMA Female

Buzzer for sound indications

USB or 240/110V AC/DC adapter

3W

All information is subject to change without prior notice. Availability of product variants may vary regionally.

540 g / 19.0 oz

-20 to 55 °C -4 to 130 °F

-40 to 85 °C -40 to 185 °F

IP20, for indoor use only

+30dBm (1 W) ERP

Tapping LED Sensor indicators

Buzzer

### PRODUCT HIGHLIGHTS

- Long-range and accurate RFID reading
- GPIO connector
- Three external antenna ports
- Power over USB or external power supply

#### SOFTWARE APPLICATIONS

- RFID Demo Software for testing reader capabilities
- RFID Configurator software for configuring the reader

#### SOFTWARE DEVELOPMENT

- Ready-to-use Nordic ID NUR API that provides full control over the reader
- Application can be written in C/C++, .NET languages and Java
- USB driver for: Windows: XP, Vista, 7, 8, 10, Linux, Android

#### SUITABLE APPLICATION AREAS

- Point-of-sales
- Document tracking
- Access control
- Tag programming stationsSmart shelves and smart displays
- Inventory management

#### SERVICE AND SUPPORT

- Free support during and after warranty time
  Maintenance service and extended warranty contract
- · Software customization and development support
- Technology, product and integration training
- Technology and project consultation
- Project management services

#### WARRANTY

2 year warranty Extendable up to 5 years

RAII R F I I

EU DIRECTIVE 2002/96/EC ON WASTE



CE





NORDIC ID GROUP Joensuunkatu 7 | FI-24100 Salo, FINLAND tel. +358 2 727 7700 | fax +358 2 727 7720 info@nordicid.com | www.nordicid.com GERMANY

Nordic ID GmbH | Bielefeld, GERMANY tel. +49 5206 70 84 70 | fax +49 5206 70 847 10 info@nordicid.de | www.nordicid.de V18