
EVOOQ

INFINITELY INNOVATIVE



CONFIGURATIONS



EV646E

EV456K

EVOQ

| | |
|-------------|---|
| Cooling | FANLESS |
| Frame | Aluminium |
| Screen | 15.6" True Flat 16/9 LED |
| | Full HD IPS |
| Resolution | 1920 x 1080 |
| Touch panel | Multi-Touch (PCAP) |
| Memory RAM | 1 x DDR4 4GB 2133MHz SO-DIMM (1 Slot 16 GB Max) |
| Storage | 1 x M.2 SSD 128 GB |

MODEL

EV646E

| | |
|--------------------|-------------------------|
| Processor | Intel Elkhart Lake 6412 |
| Graphic controller | Intel HD Graphic 12.1 |
| Graphic memory | Shared |
| Network controller | Realtek PCIe GBE |
| Audio controller | Realtek ALC662-HD Audio |

EV456K

| | |
|--------------------|----------------------------|
| Processor | Intel Tiger Lake i3-1115G4 |
| Graphic controller | Intel HD Graphic 12.1 |
| Graphic memory | Shared |
| Network controller | Realtek PCIe GBE |
| Audio controller | Realtek ALC662-HD Audio |

OS COMPATIBLES

Windows 11

Windows 10 (64 bits)

INPUT/OUTPUT

| | |
|------------------|---------------------------------|
| Network | 1 x RJ45 |
| Connectors | 2 x M.2 SSD ou NVMe (M-key) |
| USB Type A | 2 x USB 3.0 |
| | 3 x USB 2.0 (1 in front) |
| USB Type C | 2 |
| FeDP | 2 |
| Serial COM RS232 | 2 (COM1 & COM2 DB9-COM+5V/+12V) |
| Cash drawer | 1 x 12V/24V |
| DC-IN | 1 x 4 pin w/lock |
| Power supply | 90W/19V |

VARIOUS

| | |
|-----------------------|--------------------------------|
| Dimensions l x L x H | 328 x 262 x 339 mm |
| Weight | 4.5kg |
| Colours | Black |
| Setup | Horizontal from 0° to 90° |
| Certifications | FCC/CE Class A, LVD |
| Operating temperature | 0°C ~ 35°C |
| Storage temperature | -10°C ~ 50°C |
| Humidity | 20% ~ 85% without condensation |

PACKAGING

| | |
|----------------------|-------------------|
| Unit | 1 |
| Dimensions l x L x H | 478 x 323 x 495mm |
| Weight | 6.5kg |

OPTIONS

- Integrated customer display
- 2nd capacitive screen 11.6"
- 2nd screen 11.6"
- 2D scanner reader
- ISO 1/2/3 (MSR) barcode
- Dallas reader (I-BUTTON)
- Fingerprint reader
- Hub USB retail 1 x 24V 2 x 12V



Specifications are subject to change without notice. © OXHOO 2022



EVOOQ

INFINITELY INNOVATIVE



4:3
SCREEN


CAPACITIVE
MULTI-TOUCH




MICROSOFT


FANLESS


SSD
M.2


NVMe
M.2

CONFIGURATIONS



EVOQ

| | |
|-------------|---|
| Cooling | FANLESS |
| Frame | Aluminium |
| Screen | 15.1" True Flat 4/3 LED |
| Resolution | 1024 x 768 |
| Touch panel | Multi-Touch (PCAP) |
| Memory RAM | 1 x DDR4 4GB 2133MHz SO-DIMM (1 Slot 16 GB Max) |
| Storage | 1 x M.2 SSD 128 GB |

MODEL

EV395K

| | |
|--------------------|-------------------------------|
| Processor | Intel Kaby Lake Celeron 3965U |
| Graphic controller | Intel HD Graphic DX12 |
| Graphic memory | Partagée |
| Network controller | Realtek PCIe GBE |
| Audio controller | Realtek ALC662-HD Audio |

EV645E

| | |
|--------------------|-------------------------|
| Processor | Intel Elkhart Lake 6412 |
| Graphic controller | Intel HD Graphic 12.1 |
| Graphic memory | Shared |
| Network controller | Realtek PCIe GBE |
| Audio controller | Realtek ALC662-HD Audio |

EV455K

| | |
|--------------------|----------------------------|
| Processor | Intel Tiger Lake i3-1115G4 |
| Graphic controller | Intel HD Graphic 12.1 |
| Graphic memory | Shared |
| Network controller | Realtek PCIe GBE |
| Audio controller | Realtek ALC662-HD Audio |

OS COMPATIBLES

Windows 11
Windows 10 (64 bits)

INPUT/OUTPUT

| | |
|------------------|---|
| Network | 1 x RJ45 |
| Connectors | 2 x M.2 SSD ou NVMe (M-key) |
| USB Type A | 2 x USB 3.0 3 x USB 2.0 (1 in front) |
| USB Type C | 2 |
| FeDP | 2 |
| Serial COM RS232 | 2 (COM1 & COM2 DB9-COM+5V/+12V) |
| Cash drawer | 1 x 12V/24V |
| DC-IN | 1 x 4 pin w/lock |
| Power supply | 90W/19V |

VARIOUS

| | |
|-----------------------|--------------------------------|
| Dimensions l x L x H | 328 x 262 x 339 mm |
| Weight | 4.5kg |
| Colours | Black |
| Setup | Horizontal from 0° to 90° |
| Certifications | FCC/CE Class A, LVD |
| Operating temperature | 0°C ~ 35°C |
| Storage temperature | -10°C ~ 50°C |
| Humidity | 20% ~ 85% without condensation |

PACKAGING

| | |
|----------------------|-------------------|
| Unit | 1 |
| Dimensions l x L x H | 478 x 323 x 495mm |
| Weight | 6.5kg |

OPTIONS

| |
|---|
| Integrated customer display |
| 2 nd capacitive screen 11.6" |
| 2 nd screen 11.6" |
| 2D scanner reader |
| ISO 1/2/3 (MSR) barcode |
| Fingerprint reader |
| Hub USB retail 1 x 24V 2 x 12V |



Specifications are subject to change without notice. © OXHOO 2022

