



CARE . TRUST . RESPONSIBILITY

# RECEIPT PRINTER RP-700

MINI THERMAL PRINTER



RP-700 is the most efficient and elegant thermal receipt printer for retail and hospitality environment. Its high speed, compact size and support of both Front/Top receipt printout are suitable for any diversified environment, especially for stores that are looking for tidy table and space utilization. It is specially designed for flexible operation in both under or above counter operation mode.

Maximum protection against dust and liquid splashes can also be applied through its Front receipt printout mode, which are critical in extreme environment such as restaurants, bars, kitchens...etc.

RP-700 features in trendy outlook with glossy Black or White selections. Its Triple-Interface connectivity is capable of connecting any terminals hassle-free. With Apple certified "MFi", RP-700 can be paired with Apple iPad®, iPhone® and iPod Touch® hassle-free (optional connectivity).



Made for

iPod iPhone iPad

## SPECIAL FEATURES

- 58-80mm paper printing width receipt Printer (2/3inch)
- Small footprint with dimension 127mm x 127mm x 134mm (LxWxH)
- Front paper load & Top paper load (BOTH)
- Resolution 203 dpi
- 250mm/sec high speed printing
- Multiple interfaces : ● USB+Serial+Ethernet ● USB+BT ( Apple MFi certified)
- Selection of Glossy Black and Glossy White
- Energy Star certified
- JAVAPOS/OPOS/Linux support

**RP-700**

| Item        |                        | RP-700                                              |
|-------------|------------------------|-----------------------------------------------------|
| Printing    | Method                 | Direct Thermal                                      |
|             | Paper Loading Scenario | Top and Front                                       |
|             | Speed                  | 250mm/sec                                           |
|             | Width                  | Max 80mm                                            |
|             | Resolution             | 203DPI                                              |
| Paper       | Type                   | Thermal Paper                                       |
|             | Width                  | 57.5/80/82.5mm                                      |
|             | Thickness              | 0.06mm~0.1mm                                        |
|             | Roll Diameter          | Max. 83mm                                           |
|             | Roll Core Inner        | 12.5mm                                              |
| Memory      |                        | RAM : 2MB, Flash : 4MB                              |
| Reliability | TPH Life               | 150km                                               |
|             | MCBF                   | 70,000,000 Lines                                    |
| Auto cutter |                        | 2,000,000 cuts                                      |
| Sensor      |                        | Paper End, Cover Open, Black Mark, Paper Near End   |
| Interface   |                        | * USB+Serial+Ethernet<br>* USB+BT ("Mfi" certified) |
| Emulation   |                        | ESC/POS Command Compatible                          |
| Driver      |                        | Windows, MAC<br>LinuxCUPS, OPOS, JavaPOS            |
| Power       | Type                   | External Adaptor                                    |
|             | AC                     | 100~240Vac 50/60 Hz                                 |
|             | DC                     | 24Vdc / 2.5A                                        |
| Temperature |                        | Operation 5°C ~ 45°C                                |
|             |                        | Storage -40°C ~60°C                                 |
| Dimension   |                        | 127mm x 127mm x 134mm(LxWxH)                        |
| Weight      |                        | 1 kg                                                |
| Color       |                        | Black / White                                       |
| Certificate |                        | FCC, CE, CB, 3C, VCCI, MFi, Energy Star             |

\*Specification is subject to change without prior notice



TAIWAN E-mail:sales@partner.com.tw  
 USA E-mail:sales@partnertechcorp.com  
 EUROPE E-mail:info@partner-tech.eu  
 UK E-mail:sales@partnertechuk.com  
 CHINA E-mail:sales@partnertech.com.cn  
 JAPAN E-mail:sales-jp@partner.com.tw

SOUTH AFRICA E-mail:sales@partnertech.co.za  
 NORTH AFRICA E-mail:sales@partnertechna.com  
 MIDDLE EAST E-mail:info@partnertechme.com  
 AUSTRALIA E-mail:sales@partner-tech.com.au  
 SOUTH EAST ASIA E-mail:ptse@partner.com.tw