



# 1128 **BLUETOOTH**<sup>®</sup> UHF RFID READER

## HIGH PERFORMANCE, **BLUETOOTH**<sup>®</sup> WIRELESS ENABLED UHF RFID READER



RFID-only Antenna with Slimline Grip



Trigger Handle and 2D UHF antenna



Custom Mount for Datalogic Skorpion X3



Modular design



### Data Collection Performance Like No Other

The TSL<sup>®</sup> 1128 *Bluetooth*<sup>®</sup> UHF RFID reader provides new levels of RFID performance. With its R2000 core and range of interchangeable high performance antennas, the 1128 performs like no other reader giving the user the highest levels of flexibility currently available in today's market. Designed to read and write to EPC Class 1 Gen 2 (ISO18000-6C) tags, the 1128 can also be configured with class leading high performance 2D barcode data scanning to bring unparalleled data collection capabilities to any host it is connected to. The 2D imager engine incorporates fast-pulse illumination and fast sensor shutter speeds, delivering outstanding motion tolerance and class leading 1D and 2D data capture.

### Platform Independent UHF RFID Reader

Use existing *Bluetooth*<sup>®</sup> wireless technology enabled<sup>1</sup> host devices including Enterprise Handhelds, Consumer Phones, Touchscreen MP3 players, Tablets and PC's – the 1128 will bring high performance RFID and 2D scanning to all these devices running a wide range of Operating Systems. The 1128 *Bluetooth*<sup>®</sup> UHF RFID reader can also be tethered to a PC using a USB cable.

Extensive software support is available for a wide range of platforms including code samples, demonstration applications and source code.

### As Easy As ABC....

The new 1128 *Bluetooth*<sup>®</sup> UHF RFID reader incorporates TSL's unique ASCII protocol for faster and easier application development. This sophisticated parameterised ASCII protocol provides the developer a powerful set of commands that carry out multiple actions locally within the reader. This approach enables multiple tag operations executed using simple pre-configured ASCII commands which not only speeds integration of the reader into applications but also abstracts the developer from some of the complexities of the underlying Native API and ultimately results in un-paralleled levels of performance.

### A Configuration To Suit Your Application

The choice of host device is yours - from low cost touchscreen MP3 players through to fully featured Enterprise Handheld Terminals. The choice of ergonomic style includes a compact slimline grip through to a comfortable trigger handle for scan intensive RFID and 2D bar code data collection applications.

EPC data can be stored on an optional Micro SD memory card (up to 500 million transponder EPCs on a 32GB card - separate purchase from alternative supplier). This provides the ability to collect and log data even if USB or *Bluetooth*<sup>®</sup> communication channels are not available.

### Features:

#### High Performance *Bluetooth*<sup>®</sup> Multi-modal Data Capture

UHF RFID and 2D barcode data capture in one integrated *Bluetooth*<sup>®</sup> device.

#### Hardware Platform Independence

Operates with wide variety of *Bluetooth*<sup>®</sup> wireless technology enabled host devices including touchscreen MP3 players, phones, tablets, Enterprise Handhelds and PC's.

#### OS Independence

Operates with Android, iOS, Windows 10, 8, 7, Vista, XP, Windows Mobile, Windows CE, and Windows Phone.

#### Batch Data Collection

Removable high capacity Micro SD data card and real time clock for extended batch data collection independent of host connection.

#### Flexible Configuration

Unique interchangeable high performance antennas including optional 2D scanning and trigger handle with a range of device specific mounts for holding phones and MP3 players.

#### High Performance Barcode Scanning

Integrated 2D imaging engine provides class leading barcode scan performance via its unique patent pending fast pulse illumination which delivers outstanding motion tolerance and class leading 1D and 2D data capture

## Physical and Environmental Characteristics

|                         |   |
|-------------------------|---|
| Dimensions (LxWxH):     | 16.0 cm x 7.7 cm x 16.9 cm – Trigger handle.<br>16.0 cm x 7.7 cm x 9.7 cm – Slimline grip.  |
| Weight:                 | 375 g / 13.2 oz (including battery & trigger handle).   |
| User input:             | Trigger button.   |
| User feedback:          | Speaker, vibration motor, LED.  |
| Power:                  | Removable, rechargeable 3.7V, 2400mAh, 8.9Wh Lithium Polymer battery pack.  |
| Minimum operating time: | Light use <sup>1</sup> : 9 hrs<br>Moderate use <sup>2</sup> : 5 hrs<br>Heavy use <sup>3</sup> : 2.5 hrs<br><small><sup>1</sup>Light Use: Continuous RFID inventories for 20s of every 120s<br/><sup>2</sup>Moderate Use: Continuous RFID inventories for 10s of every 30s<br/><sup>3</sup>Heavy Use: Continuous RFID inventories for 59s of every 60s</small> |
| Enclosure materials:    | Polycarbonate.  |

## Performance Characteristics

|  |  |
|--|--|
| RFID engine:                                       | TSL <sup>®</sup> custom module with embedded Impinj R2000.   |
| Communication protocols:                           | TSL <sup>®</sup> ASCII 2.0 parameterised command set<br>Impinj binary.   |
| Memory:  | Optional Micro SD card (maximum 32GB capacity supported). Up to 500 million date and time stamped EPCs can be stored on a 32GB Micro SD card (separate purchase from alternative supplier).                                    |
| Compatible Host devices (Bluetooth <sup>®</sup> ): | Any Bluetooth <sup>®</sup> Host <sup>1</sup> supporting the Serial Port Profile (SPP) or Human Interface Device (HID) profile (Android, iOS, Linux, Mac, Windows). See <a href="#">Bluetooth<sup>®</sup> Mode Comparison</a> . |
| Compatible Host devices (USB):                     | Any USB host with FTDI VCP driver support (Windows, Linux, Mac, Android).  |

## Environmental

|                                |  |
|--------------------------------|--|
| Operating Temp.:               | -10°C to 40°C (14°F to 104°F).   |
| Charging Temp.:                | 5°C to 40°C (41°F to 104°F).   |
| Storage Temp.:                 | Less than 1 month at -20°C to +45°C (-4°F to 113°F).<br>Less than 6 months at -20°C to +35°C (-4°F to 95°F). |
| Humidity:                      | 5% to 85% non-condensing.  |
| Drop Spec:                     | Multiple drops to concrete: 4 ft./1.2 m ambient, 3ft / 0.9m across the operating temperature range.          |
| Tumble:                        | 500 0.5 metre tumbles at room temperature (1,000 cycles).  |
| Environmental Sealing:         | IP54.  |
| Electrostatic Discharge (ESD): | ± 15kVdc air discharge; ± 8kVdc contact discharge.   |
| MIL-STD 810F:                  | Meets and exceeds applicable MIL-STD 810F for drop, tumble and sealing.                                      |

## RFID Performance

|                                    |                      |
|------------------------------------|----------------------|
| Standards supported:               | EPC Class 1 Gen 2.   |
| Nominal read range <sup>2</sup> :  | Up to 5.5 m (18 ft). |
| Nominal write range <sup>2</sup> : | Up to 2 m (6.5 ft).  |

|                       |  |
|-----------------------|--|
| Field:                | 150-degree forward facing (approx.) measured from front of device. |
| Antenna:              | Detachable, Circularly Polarized with optional 2D scanner.         |
| Frequency Range:      | EU: 865-868MHz; US: 902-928MHz.<br>See Page 5 for other regions.   |
| Maximum Output Power: | Up to 29 dBm (region dependant)<br>+ 3.0 dBiC Antenna              |
| Antenna options:      | High Performance CP.<br>High Performance CP with 2D Imager.        |

## Barcode Scanning

|                             |  |             |            |
|-----------------------------|--|-------------|------------|
| Optional 2D Barcode Engine: | Optional TSL <sup>®</sup> custom 2D Barcode Scan Engine module.  |             |            |
| Sensor Resolution:          | 1280 x 960 pixels, rolling shutter   |             |            |
| Field of View:              | Horizontal: 44.5°, vertical: 33.5°   |             |            |
| Focal Distance:             | From front of engine: 15.24 cm (6 in.)   |             |            |
| Aiming LED:                 | Green LED  |             |            |
| Illumination:               | 1 warm white LED   |             |            |
| Symbologies Supported:      | 1D: All major codes<br>2D: PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal, Dutch Postal (KIX). |             |            |
| Ranges <sup>3</sup> :       | <b>Barcode</b>   | <b>Near</b> | <b>Far</b> |
|                             | 5 mil Code 39  | 6.1 cm      | 24.1 cm    |
|                             | 5 mil Code 128   | 7.1 cm      | 22.9 cm    |
|                             | 6.67 mil PDF 417   | 6.1 cm      | 20.3 cm    |
|                             | 10 mil DataMatrix  | 7.4 cm      | 21.6 cm    |
|                             | 100% UPCA  | 4.6 cm      | 49.5 cm    |
|                             | 15 mil QR  | 3.0 cm      | 29.2 cm    |
|                             | 20 mil QR  | 3.0 cm      | 35.6 cm    |

## Communication

|   |  |
|---|--|
| Bluetooth <sup>®</sup> :                    | Bluetooth <sup>®</sup> Version 2.1.          |
| Bluetooth <sup>®</sup> Frequency Range:     | 2.4 - 2.4835 GHz.                            |
| Bluetooth <sup>®</sup> Profiles:            | SPP Profile, HID Profile, Apple iAP.         |
| Bluetooth <sup>®</sup> Power:               | Class 2.                                     |
| Bluetooth <sup>®</sup> TX Power:            | 3 dBm.                                       |
| Bluetooth <sup>®</sup> Range <sup>4</sup> : | 30 m.  |
| Bluetooth <sup>®</sup> Pairing:             | PIN, Simple Secure Pairing, NFC OOB Pairing. |

<sup>1</sup> Compatible Bluetooth<sup>®</sup> stack required in the Host device

<sup>2</sup> Tag Read/Write performance is dependent on tag type, items tagged, number of tags in the field and other radio and environmental factors

<sup>3</sup> Artificial lighting can affect scanning performance

<sup>4</sup> Open field

## Peripherals and Accessories

|                      |   |
|----------------------|---|
| External interface:  | MicroUSB connector for battery charging, and USB connectivity.  |
| USB operating modes: | Tethered for real time data capture in conjunction with SmartWedge software. Download of stored scan data.                                    |
| Optional charger:    | TSL® 2136 4-Slot desktop charger.   |
| Other Accessories:   | Adapter mounts are available for a variety of smartphones handheld terminals. Slimline Grip, Trigger Handle. See page 6 for more information. |

## Regulatory

|                   |  |
|-------------------|--|
| Regions           | EU (CE), USA (FCC), Canada, Australia and more (see page 5 for details)  |
| FCC ID            | S6J1128  |
| IC                | 8948A-1128   |
| EMC               | EN 55032:2015 +A11:2020<br>EN 55035:2017 +A11:2020<br>47 CFR Part 15B<br>ICES-003:2020 Issue 7   |
| RF                | EN 300 328 V2.2.2<br>EN 302 208 V3.2.0<br>EN 301 489-1 V2.2.3<br>EN 301 489-3 V2.1.1<br>EN 301 489-17 V3.2.4<br>47 CFR Part 15C 15.247<br>RSS-247 Issue 1                                      |
| Electrical Safety | IEC 62368-1:2018<br>EN 62368-1:2020 +A11:2020<br>UL 62368-1:2019<br>CAN/CSA C22.2 No. 62368-1:19   |
| Environmental     | <b>2011/65/EU (RoHS 2)</b><br>Restriction of the use of certain Hazardous Substances in electrical and electronic equipment<br><b>2015/863 (RoHS 3)</b><br>Amendment to Annex II of 2011/65/EU |

## Warranty

The TSL® 1128 reader is warranted against defects in workmanship and materials for a period of one year (12 months) from date of shipment, provided the product remains unmodified and is operated under normal and proper conditions.

## Terms

“Made for iPod,” “Made for iPhone,” and “Made for iPad” mean that an electronic accessory has been designed to connect specifically to iPod, iPhone, or iPad, respectively, and has been certified by the developer to meet Apple performance standards. Apple is not responsible for the operation of this device or its compliance with safety and regulatory standards. Please note that the use of this accessory with iPod, iPhone, or iPad may affect wireless performance.

iPad, iPhone, iPod and iPod touch are trademarks of Apple Inc., registered in the U.S. and other countries.

The *Bluetooth*® word mark and logos are registered trademarks owned by *Bluetooth* SIG, Inc. and any use of such marks by Technology Solutions UK Ltd is under license. Other trademarks and trade names are those of their respective owners.

## TSL® RFID Apps



RFID Explorer  
[www.tsl.com/apps/rfid-explorer](http://www.tsl.com/apps/rfid-explorer)



RFID Scan Scan Write  
[www.tsl.com/apps/rfid-scan-scan-write](http://www.tsl.com/apps/rfid-scan-scan-write)



RFID Tag Finder  
[www.tsl.com/apps/rfid-tag-finder](http://www.tsl.com/apps/rfid-tag-finder)



TSL® Reader Configuration  
[www.tsl.com/apps/tsl-reader-configuration](http://www.tsl.com/apps/tsl-reader-configuration)



RFID Web Wedge  
[www.tsl.com/apps/rfid-web-wedge](http://www.tsl.com/apps/rfid-web-wedge)

# EXAMPLE CONFIGURATIONS



With Honeywell Dolphin D75e



With Apple iPod touch® (4th & 5th gen)



With Motorola ES400



With *Bluetooth*® wireless technology enabled computer



With Samsung Galaxy Tab S



With iPhone 6 Plus

# 1128 PART NUMBER LIST

| Countries   |   |  | Part Numbers   | Operating Frequency  |
|---|---|--|--|--|
| Albania<br>Andorra<br>Austria<br>Belgium<br>Bosnia & Herzegovina<br>Bulgaria<br>Bhutan<br>Croatia<br>Cyprus<br>Czech Republic<br>Denmark<br>Estonia<br>Falkland Islands<br>Finland<br>France<br>French Guiana | Georgia<br>Germany<br>Greece<br>Greenland<br>Guernsey<br>Guadeloupe<br>Hungary<br>Iceland<br>Ireland<br>Italy<br>Jersey<br>Latvia<br>Liechtenstein<br>Lithuania<br>Luxembourg<br>Macedonia<br>Malta | Martinique<br>Monaco<br>Montenegro<br>Netherlands<br>Norway<br>Poland<br>Portugal<br>Romania<br>Slovakia<br>Slovenia<br>Spain<br>Sweden<br>Switzerland<br>UAE<br>United Kingdom (UK) | With 2D barcode imager:<br><a href="#">1128-EU-BT-UHF-IMG</a><br><br>No barcode imager:<br><a href="#">1128-EU-BT-UHF-A1</a> | 865 – 868 MHz<br>4 Channels  |
| United States of America (USA)<br>Guam<br>Guatemala<br>Northern Mariana Islands   | Canada<br>Ecuador<br>Puerto Rico  |  | With 2D barcode imager:<br><a href="#">1128-US-BT-UHF-IMG</a><br><br>No barcode imager:<br><a href="#">1128-US-BT-UHF-A1</a> | 902 – 928 MHz<br>50 Channels   |
| Australia   |   |  | <a href="#">1128-AU-BT-UHF-IMG</a><br><a href="#">1128-AU-BT-UHF-A1</a>  | 920 – 926 MHz<br>12 Channels   |
| Bangladesh  |   |  | <a href="#">1128-BD-BT-UHF-IMG</a><br><a href="#">1128-BD-BT-UHF-A1</a>  | 925 – 927 MHz<br>4 Channels  |
| Brazil  |   |  | <a href="#">1128-BR-BT-UHF-IMG</a><br><a href="#">1128-BR-BT-UHF-A1</a>  | 902 – 907.5, 915 – 928 MHz<br>50 Channels                              |
| Chile   |   |  | <a href="#">1128-CL-BT-UHF-IMG</a><br><a href="#">1128-CL-BT-UHF-A1</a>  | 913 – 919, 925 – 928 MHz<br>14 Channels, Power Limited: 500mW EIRP Max |
| China   |   |  | <a href="#">1128-CN-BT-UHF-IMG</a><br><a href="#">1128-CN-BT-UHF-A1</a>  | 920.5 – 924.5 MHz<br>16 Channels                                       |
| Colombia  |   |  | <a href="#">1128-CO-BT-UHF-IMG</a><br><a href="#">1128-CO-BT-UHF-A1</a>  | 915 – 928 MHz<br>24 Channels   |
| El Salvador   |   |  | <a href="#">1128-SV-BT-UHF-IMG</a><br><a href="#">1128-SV-BT-UHF-A1</a>  | 915 – 928 MHz<br>24 Channels   |
| Hong Kong   |   |  | <a href="#">1128-HK-BT-UHF-IMG</a><br><a href="#">1128-HK-BT-UHF-A1</a>  | 920 – 925 MHz<br>8 Channels  |
| India   |   |  | <a href="#">1128-IN-BT-UHF-IMG</a><br><a href="#">1128-IN-BT-UHF-A1</a>  | 865 – 867 MHz<br>3 Channels  |
| Japan   |   |  | <a href="#">1128-JP-BT-UHF-IMG</a><br><a href="#">1128-JP-BT-UHF-A1</a>  | 920 – 925 MHz, 3 Channels<br>Power Limited: 500mW EIRP Max             |
| Malaysia  |   |  | <a href="#">1128-MY-BT-UHF-IMG</a><br><a href="#">1128-MY-BT-UHF-A1</a>  | 919 – 923 MHz<br>6 Channels  |
| Peru  |   |  | <a href="#">1128-PE-BT-UHF-IMG</a><br><a href="#">1128-PE-BT-UHF-A1</a>  | 916 – 928 MHz<br>23 Channels   |
| Singapore (Licence Free)  |   |  | <a href="#">1128-XS-BT-UHF-IMG</a><br><a href="#">1128-XS-BT-UHF-A1</a>  | 920 – 925 MHz<br>8 Channels, Power Limited: 500mW ERP Max              |
| Singapore (Licence Required)  |   |  | <a href="#">1128-SG-BT-UHF-IMG</a><br><a href="#">1128-SG-BT-UHF-A1</a>  | 920 – 925 MHz<br>8 Channels  |
| South Korea   |   |  | <a href="#">1128-KR-BT-UHF-IMG</a><br><a href="#">1128-KR-BT-UHF-A1</a>  | 917 – 923.5 MHz<br>6 Channels  |
| Taiwan  |   |  | <a href="#">1128-TW-BT-UHF-IMG</a><br><a href="#">1128-TW-BT-UHF-A1</a>  | 922 – 928 MHz<br>10 Channels   |
| Thailand (Licence Required)   |   |  | <a href="#">1128-TH-BT-UHF-IMG</a><br><a href="#">1128-TH-BT-UHF-A1</a>  | 920 – 925 MHz<br>8 Channels  |
| Vietnam   |   |  | <a href="#">1128-VN-BT-UHF-IMG</a><br><a href="#">1128-VN-BT-UHF-A1</a>  | 918 – 923 MHz<br>8 Channels, Power Limited: 500mW ERP Max              |

If you are interested in purchasing for a country/region that is not listed above, please contact [enquiries@tsl.com](mailto:enquiries@tsl.com) for assistance.



# 1128 PART NUMBER LIST

| Accessories                                    | Part Number              |
|--|--------------------------|
| <b>Charging and Docking</b>                    |                          |
| Docking Cradle Kit for 1128 UHF RFID Reader    | 1128-CRD-02-KIT          |
| 4-Slot Battery Charger Kit                     | 2136-01-4WMS-CHG         |
| Spare Battery for 1128/2128 UHF Reader         | 1128-00-BA-2000          |
| <b>Grip handles</b>                            |                          |
| Slimline Grip attachment.                      | 1128-SLG                 |
| <b>Holsters</b>                                |                          |
| Belt Holster for 1128 Slimline Grip            | 1128-HOLST-01-SLG        |
| Belt Holster for 1128/2128 with Trigger Handle | 1128-HOLST-01-TRG        |
| <b>Slide-on Mounts</b>                         |                          |
| iPad Mini (1 <sup>st</sup> gen) Mount          | 1128-MNT-IPADMINI        |
| iPad Mini (4 <sup>th</sup> gen) Mount          | 1128-MNT-IPADMINI4       |
| iPad Air (2 <sup>nd</sup> gen) Mount           | 1128-MNT-IPADAIR2        |
| iPhone 4 Mount                                 | 1128-MNT-IPHN4G          |
| iPhone 5 Mount                                 | 1128-MNT-IPHN5G          |
| iPhone 6 (4.7") Mount                          | 1128-MNT-IPHN6G          |
| iPhone 6 Plus (5.5") Mount                     | 1128-MNT-IPHN6PLUS       |
| iPhone 7 (4.7") Mount                          | 1128-MNT-IPHN7G          |
| iPhone 7 Plus (5.5") Mount                     | 1128-MNT-IPHN7PLUS       |
| iPhone 8 (4.7") Mount                          | 1128-MNT-IPHN8G          |
| iPhone 8 Plus (5.5") Mount                     | 1128-MNT-IPHN8PLUS       |
| iPhone 11 Mount                                | 1128-MNT-IPHN-11         |
| iPhone 11 Pro Mount                            | 1128-MNT-IPHN-11-PRO     |
| iPhone 11 Pro Max Mount                        | 1128-MNT-IPHN-11-PRO-MAX |
| iPhone 12 Mount                                | 1128-MNT-IPHN-12         |
| iPhone 12 Mini Mount                           | 1128-MNT-IPHN12-MINI     |
| iPhone 12 Pro Max Mount                        | 1128-MNT-IPHN12-PRO-MAX  |
| iPhone 13 Mount                                | 1128-MNT-IPHN-13         |
| iPhone 13 Mini Mount                           | 1128-MNT-IPHN13-MINI     |
| iPhone 13 Pro Mount                            | 1128-MNT-IPHN13-PRO      |
| iPhone 13 Pro Max Mount                        | 1128-MNT-IPHN13-PRO-MAX  |
| iPhone X (5.8") Mount                          | 1128-MNT-IPHN-X          |
| iPhone XR Mount                                | 1128-MNT-IPHN-XR         |
| iPhone XS Mount                                | 1128-MNT-IPHN-XS         |
| iPhone XS Max Mount                            | 1128-MNT-IPHN-XS-MAX     |
| iPod touch (4 <sup>th</sup> gen) Mount         | 1128-MNT-IPOD4G          |
| iPod touch (5 <sup>th</sup> gen) Mount         | 1128-MNT-IPOD5G          |
| iPod touch (6 <sup>th</sup> gen) Mount         | 1128-MNT-IPOD6G          |
| iPod touch (7 <sup>th</sup> gen) Mount         | 1128-MNT-IPOD7G          |
| Galaxy Nexus Mount                             | 1128-MNT-NEXUS           |
| Motorola MC2100 Mount*                         | 1128-MNT-MC2100*         |
| Motorola MC40 Mount*                           | 1128-MNT-MC40*           |

|  |                      |
|--|----------------------|
| Motorola MC45 Mount*                             | 1128-MNT-MC45*       |
| Moto G (1 <sup>st</sup> gen) Mount               | 1128-MNT-MOTOG       |
| Moto G (2 <sup>nd</sup> gen) Mount               | 1128-MNT-MOTO-G-GEN2 |
| Moto G (3 <sup>rd</sup> gen) Mount               | 1128-MNT-MOTO-G-GEN3 |
| Moto G (5 <sup>th</sup> gen) Mount               | 1128-MNT-MOTO-G-GEN5 |
| Motorola ES400 Mount*                            | 1128-MNT-ES400       |
| Motorola TC55 Mount*                             | 1128-MNT-TC55-01*    |
| Samsung Galaxy J5 Mount                          | 1128-MNT-GALAXY-J5   |
| Samsung Galaxy S4 Mount                          | 1128-MNT-GALAXY-S4   |
| Samsung Galaxy S5 Mount                          | 1128-MNT-GALAXY-S5   |
| Samsung Galaxy S7 Mount                          | 1128-MNT-GALAXY-S7   |
| Nokia 1520 Mount                                 | 1128-MNT-NK1520      |
| 1128 Slide-on Pop-Loq <sup>®</sup> Mount Adapter | 1128-PL              |

\* Currently available in SLS RP materials only. Other handheld device mounts available by special request (volume dependent).

# ABOUT

## ABOUT TSL®



Technology Solutions UK Ltd (TSL®), part of HID Global, is a leading manufacturer of high performance mobile RFID readers used to identify and track products, assets, data or personnel.

For over two decades, TSL® has delivered innovative data capture solutions to Fortune 500 companies around the world using a global network of distributors and system integrators. Specialist in-house teams design all aspects of the finished products and software ecosystems, including electronics, firmware, application development tools, RF design and injection mould tooling.

TSL® is an ISO 9001:2015 certified company.



ISO 9001: 2015

## CONTACT

**Address:** Technology Solutions (UK) Ltd, Suite A, Loughborough Technology Centre, Epinal Way, Loughborough, Leicestershire, LE11 3GE, United Kingdom.

**Telephone:** +44 1509 238248

**Fax:** +44 1509 214144

**Email:** [enquiries@tsl.com](mailto:enquiries@tsl.com)

**Website:** [www.tsl.com](http://www.tsl.com)

## ABOUT HID GLOBAL



**HID Global powers the trusted identities of the world's people, places and things.** We make it possible for people to transact safely, work productively and travel freely. Our trusted identity solutions give **people** convenient access to physical and digital **places** and connect **things** that can be identified, verified and tracked digitally. Millions of people around the world use HID products and services to navigate their everyday lives, and billions of things are connected through HID technology. We work with governments, educational institutions, hospitals, financial institutions, industrial businesses and some of the most innovative companies on the planet. Headquartered in Austin, Texas, HID Global has over 4,000 employees worldwide and operates international offices that support more than 100 countries. HID Global is an ASSA ABLOY Group brand.

For more information, visit [www.hidglobal.com](http://www.hidglobal.com).