













6-slot charging cradle



**UHF RFID reader** 



**Gun Grip** 



**Charging cradle** for gun grip

## **RETHINK** your idea of a rugged enterprise mobile computer with the **SLEEK DESIGN** of the EA500P(Plus)

The unitech EA500P (Plus) Android 8 comes with the Google GMS license. It is a rugged 5" mobile enterprise computer within a compact stylish design. The EA500P (Plus) combines strong features with powerful data collection. It provides convenient connectivity (with fast roaming), reading capabilities and enhances the service level for a variety of vertical applications within the retail, hospitality, healthcare and field service sectors.





The Unitech EA500P (Plus) supports Dual-Sim. A great way to manages business and personal numbers within the same device or you can add a local data plan while traveling outside of your home country or region.



### Allrouder

Thanks to POGO pins and USB-C connerctor on the bottom side, the EA500P (Plus) has limitless scalability options for future accessories such as gun grip and docking stations.



### Compact design enterprise format

EA500P (Plus) is one of the most flexible and sleek enterprise mobile computer with a weight of only 210q.



### Choose your engine

The EA500P (Plus) gives your workforce the technology it needs to take your business to the next level. The EA500P (Plus) is available with a Basic 2D imager or Premium 2D imager.

### **Operation System**

1.4GHz, Qualcomm 8940 octa core 64 bits processor

Memory RAM 2GB/4GB optional ROM 16GB/64GB optional OS **Android 8 with GMS** 

Google Enterprise Device certified

SIM Dual Sim Languages Multi-language

Input Chinese/ English, supports handwriting Others

and soft keyboard.

### Display

5.0 inch TFT-LCD HD (720 x 1280) color screen, 300nits, Gorilla Glass 3. Ultra sensitive capacitive touch screen, compatible with gloves and supports wet resistance.

### Camera/Photos/Video

2MP front camera

13MP rear camera with LED flash and auto-focus function

### Indicator

LED's and vibration

### Communication

USB USB Type C OTG

Yes, over USB Type C POGO PIN

Charging via cradle and USB client IEEE 802.11a/b/g/n/ac/d/e/f/h/i/k/v/w/r WLAN

IPV4, IPv6.

PMKID caching, 802.11r, OKC Bluetooth® 4.2 + BR/EDR + BLE **FAST ROAMING** Bluetooth® Global brands with dual SIM Slot WWAN

FDD-LTE (B1/B2/B3/B4/B5/B7/B8/B20/ 4G

B28A/B28B)

WCDMA(B1/B2/B5/B8) 3G (2100, 1900,850, 900 MHz) GSM/EDGE/GPRS 2G (850, 900, 1800, 1900 MHz)

**GPS** GPS, AGPS, BeiDou, GLONASS

Sensors Acceleration, motion, proximity sensor, light sensor,

G-sensor, digital compass (E-compass), pressure sensor, gyroscope and height meter

Vibration 5Hz to 2KHz,60 minute duration per axis, 3 axis

### WiFi Security

802.1x(EAP): EAP-TLS, EAP-TTLS, PEAP-MSCHAPv2, WLAN Security:

PEAP-TLS, PEAP-GTC, PWD, SIM, AKA

WEP, WPA/WPA2-PSK Encryption:

### **Buttons**

5 keys- Programmable function button; dual dedicated scan buttons; volume up/down buttons; on/off button

# EA500P(PLUS)

v1.1 Specifications

### **Software Support**















SOTI Team Viewer airwatch Zello

**Data capture 2D IMAGER** 

BASIC 2D: Zebra SE2100

Support all major 1D and 2D barcodes

PREMIUM 2D: Honeywell N6603 engine.

White illumination

High Visibility Laser Aimer

Fast scan speed

Ultra-fast motion tolerance up to 5 meters p/s

Supports color barcodes Supports poorly printed barcodes Supports 1D, 2D and OCR

Symbology/X-Dim Typical Range\*

100% U.P.C 46 mm - 419 mm 5 mil Code 39 64 mm - 163 mm 28 mm - 338 mm 10 mil Code 39 46 mm - 185 mm 6.7 mm PDF417 10 mil Data Matrix 53 mm - 203 mm

Resolution linear barcodes: 0.127 mm Resolution 2D matrix codes: 0.169 mm

**HF/NFC** Frequency 13.56Mhz

Support: ISO14443A/B, ISO15693 standard,

Supports NFC

**Power Source** 

Rechargeable and Changeable (Non-swappable) Main battery 3.8V 4000mAh (typical)

3.8V 3800mAh (minimum)

Operation time 10-12 hours

(depending on the specific environment)

RTC battery Real time clock battery

### **Audio**

Microphone, speaker and 3.5mm audio jack. Support noise cancellation, PPT headset support, cellular circuit switch voice.

### **Enclosure**

155.8 mm x 76.2 mm x 13.5 mm Dimension

Weight 210g with battery

### **Environmental**

-10°C to +50°C Operating temperature Storage temperature -20°C to +70°C 0°C to 40°C Charging Temperature

Relative Humidity 5% ~ 95% (non-condensing) **Drop Specification** 1.5m drop to concrete at room temperature per MIL-STD810G

Sealing

1.0m tumble for 200 cycles and 400 times Tumble

ESD 8K / 15KV

### Device supported MDM

SOTI, AirWatch, 42Gears and MoboLink

### **Regulatory Approvals**

CE, RED, NCC, BSMI, CCC, VCCI, FCC

### **Accessories**

USB type C cable / adaptor 1-slot charging cradle Power adaptor 6-slot charging cradle Sylus Gun gripHandstrap Glass Screen protector Charging cradle for gun grip Vehicle cradle RP100 UHF/RFID Reader

Screw mount for vehicle cradle Suction mount for vehicle cradle

Heavy Duty suction mount for vehicle cradle



**Unitech Europe** 

Tilburg, The Netherlands • Tel.: +31 (0)13 460 9292 • Email: Info@eu.ute.com • Website: http://eu.ute.com