

# Z-Perform™ 1000T 150 Tag

Media Type	Label			
	Receipt			
	Tag	✓		
	Wristband			
Material Type	Paper	✓		
	Synthetic			
Printing Technology	Direct Thermal (no Ribbon Required)			
	Thermal Transfer (Ribbon Required)	<b>✓</b>		
Finish	Matte	1		
	Gloss			

	Permanent	
Adhesive Type	Removable	
.,,,,,	No Adhesive	✓
Environment	Indoor	✓
	Outdoor	
Properties	Cold Temperature	✓
	Deep Freeze	✓
	High Temperature	
	Ultra High Temperature	
	High Tack	
	Chemical Resistance	-

### **Additional Features**

- Good print quality when printed with Zebra 2300, 2100 and 3200 ribbons with a recommended Zebra printer
- BPA free

## **Suggested Applications**

- Indoor cold temperature labelling
- Visitor identification tags
- Admission tickets
- Warehouse and inventory control tags
- Shop floor / work in progress tracking tickets
- Shelf-edge tags
- Packaging inserts
- Pallet tags



## **Technical Specifications**

	Description		Caliper
Facestock	135gsm matte white uncoated paper		135 microns
		Total	135 microns ±10%

**Recommended Zebra Printers:** Desktop, mid-range and high-performance

thermal printers

**Recommended Zebra Ribbons:** 2300, 2100, 3200

Minimum Application Temperature: 0°C

When the label is applied, the environment and surface should be above this temperature

Service Temperature Range: -43°C to 93°C

Following correct application and appropriate dwell time (usually 24hrs) the media will withstand this temperature range

**Recommended Storage Conditions:** 1 year duration when stored at 0°C to 21°C

Storage of product before use at 35% to 50% RH

**Expected Life Span in Application:** Indoor use, for 1 year+

Following correct application and appropriate dwell time (usually 24hrs) we expect, but do not warrant, a life span as indicated

### **Product Performance and Suitability**

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

For testing of this material please order sample roll SAMPLE33637.