


JANAM XT30-HC



Janam's XT30-HC rugged touch computer is purpose-built for healthcare and helps to improve clinician productivity, streamline operations and elevate patient care. With XT30-HC, healthcare organizations can quickly and accurately access patient records, safely deliver medication and easily track and manage biological specimens.

Sleek but tough, XT30-HC is designed with antimicrobial housing to withstand frequent cleaning with a wide selection of disinfectants and reduce the spread of harmful microorganisms. XT30-HC is equipped with advanced features to provide the highest quality patient care, including superior barcode scanning and RFID/NFC technology, push-to-talk and VoIP voice capabilities and dual-band Wi-Fi with Fast Roaming.




POWERED BY ANDROID

Blazing fast architecture, upgradeable to future versions of Android OS



BRILLIANT DISPLAY

Easily view patient data with brilliant 5" screen



RUGGED DESIGN

Sealed to IP65 standards and withstands 6-foot drops to hospital floor




HIGH-PERFORMANCE DATA CAPTURE

Reads all 1D/2D barcodes, RFID/NFC-enabled tags on wristbands, vials, medical records and supplies



HIGH-CAPACITY BATTERY

Powerful 4500mAh removable and rechargeable battery enables extended-shift use



POWERFUL PROCESSOR

Qualcomm's Snapdragon 2.2GHz octa-core processor drives lightning-fast speeds



ULTRA-RELIABLE CONNECTIVITY

Integrated 4G, LTE, Wi-Fi with Fast Roaming, 2x2 MU-MIMO technology, Bluetooth



XT30-HC Specifications

TECHNICAL

Operating System	Android 9 with Google Mobile Services (GMS)
Processor	2.2GHz Qualcomm Snapdragon™ 660 octa-core
Memory	4GB LPDDR3 RAM/64GB eMMC Flash
Expansion	User-accessible microSD card slot with SD and SDHC support
Power	4500mAh rechargeable Li-ion battery

PHYSICAL

Dimension	6.0" L x 3.0" W x .7" D / 152mm L x 76mm W x 18mm D
Weight	9.8oz / 280g including battery
Display	5.0" High Definition (720x1280) TFT-LCD with Corning® Gorilla® Glass 3
Touch Panel	Capacitive touch screen

ENVIRONMENTAL

Operating Temperature	14° to 122° F / -10° to 50° C
Storage Temperature	-4° to 158° F / -20° to 70° C
Humidity	Non-condensing, 95%
Drop	Multiple 6ft / 1.8m drops to concrete on all sides across a wide temperature range
Water & Dust	IP65
Electro Static Discharge (ESD)	+/- 15kV air; +/- 8kV contact

INTERFACE FEATURES

Audio	3.5mm headset jack; speaker; microphone, push-to-talk (PTT) supported
Alerts	Vibration; LED indicators
LED Indicators	Dual-color
External Buttons	Side scan triggers; Volume up/down; Power button; Function key
Motion Sensor	Accelerometer; Light Sensor; Proximity Sensor

SAFETY / REGULATORY

Safety	IEC 60950; EMC; RF; SAR; LED; Laser
Radio	FCC; IC; GCF & PTCRB; CE
Environmental	RoHS and WEEE compliant

DATA CAPTURE

Imager	Honeywell N6603 1D/2D imager
RFID/NFC	Reads ISO14443 Type A; ISO14443 Type B; ISO15693; NFC on the 13.56 MHz range
Camera	8.0MP color rear-facing autofocus camera with user-controllable LED flash and 2.0MP front-facing camera

NETWORK COMMUNICATION

USB	microUSB
WWAN	FDD-LTE: B1/B2/B3/B4/B5/B7/B8/B20/B28A/B28B WCDMA: B1/B2/B5/B8 GSM/EDGE/GPRS: 850/900/1800/1900
WLAN	802.11a/b/g/n/ac/d/e/f/h/i/k/r/v
Security	IEEE 802.11n; WEP / WPA / WPA2; PEAP/MS-CHAPv2, EAP-TLS
WPAN	Bluetooth v4.1 + BR/EDR + BLE
GPS	GPS; A-GPS; Bei-Dou satellite navigation system

ACCESSORIES

Single-Slot USB /Charging Cradle Kit
Four-Slot Charging Cradle Kit
Four-Slot Battery Charging Kit
Charging Adapter



Janam Technologies
100 Crossways Park West
Suite 105
Woodbury, NY 11797

Phone: +1.877.JANAM.99
Local: +1.516.677.9500
Fax: +1.516.320.8031
Email: inquiries@janam.com

Contact Technical Support:
NA: +1.866.915.5311
EMEA: +44.1202.946945
Email: janamcare@janam.com