













1D & 2D

Android

7" screen

Megapixel

USB

Touchscreen



Micro SD



Camera









4G

PoE Bluetooth

RFID



NFC



I/O Ctrl







2 Years



WIFI Dual Band



Features

Android OS.

The NQuire 750 Stingray uses Android 7.1 OS. With this reliable operating system comes a feature-rich environment for stable apps that are tried and tested. Android 7.1 is an excellent match for the applications most suited to the NQuire 750. Particularly when operating within four walls, fitting the NQuire 750's PoE (Power over Ethernet) connectivity.

Free MDM included.

The NQuire 750 Stingray comes with the option of running Newland's free MDM solution: Ndevor. As a result, the Micro Kiosk lends itself perfectly for the coordination of multiple units. Managing information from a shared database, organizing applications and settings across many individual units, as well as lowtouch assistance in troubleshooting can all be managed from a centralized location.

Mount anywhere.

The NQuire 750 Stingray's slimline and lightweight design is suitable for mounting on any shelf edge. Options to mount the NQuire series range from shelf to wall and free-standing. Its classic Vesa75 configuration also ensures existing industry standard, 3rd party solutions are compatible.

Snappy Megapixel Scanning.

Jarcode data capture is at the heart of Newland's Micro Kiosks and so the

NQuire 750 is fitted with their own Megapixel scanning technology. This maintains high standards for the scanning of both large and small 1D & 2D barcodes. The Micro Kiosk further includes optimal settings for reading barcodes presented on smartphone and tablet screens. With the scanner set at a 20° angle, it matches the ergonomics of how the user presents codes for scanning.

Multi-purpose display.

The sharp, full-colour screen on the Stingray is perfect for running animations and live recorded videos when not actively being used. With onboard memory, expanded memory and online options, the choice of content to display is virtually limitless

Endless communication possibilities.

With WiFi, Ethernet, Powered Ethernet (PoE) and Bluetooth, this Micro Kiosk offers a variety of standard communication possibilities. Additionally, optional 4G means that the NQuire 750 Stingray can communicate and be communicated with, no matter the circumstance. Adding to that the wide variety of data capture options, such as integrated barcode reading, MSR, NFC and low frequency RFID, application possibilities are endless.

Modules can only be ordered pre-mounted to the connector on the left or right side.

Suggested industries







Healthcare









Hospitality Industrial

Manufacturing

Retail

NQuire 750 Stingray Technical specifications

Data Capture

1D All major 1D symbologies

2D All major 2D symbologies

Image Sensor CMOS 1280*800

Illumination White LED (625±10 nm)

Aiming Laser diode (625±10 nm)

Scan Modes Sense mode

Scan Rate 60 frames per second

Performance

Operating System Android 7.1

Processor 1.5GHz octa-core 64-bit

Memory RAM 2GB DDR3

Memory Flash 8GB Emmc

Memory Storage Expansion (max.) Micro SD card up to 128GB

Physical

Dimensions (mm) 195(H)x138.5(W)x25(D)mm

VESA standard Complies with the standard VESA 75 bracket, enabling easy mounting on shelves and walls

Display 7" 1280x800 IPS display

Touch Panel 5-point capacitive touch panel

Interfaces USB 2.0 host, type A port, micro USB 2.0 type B, OTG, programmable GPIO (2 in - 2 out)

Input Voltage DC12V, 2A

Power Consumption 12W (MAX)

Power Supply Input AC110 ~ 220V, 50~60Hz

Power Supply Output DC12V, 2A

Sensors G Sensor

Power over Ethernet RJ45 Ethernet, 10/100/1.000BASE-T

Audio 82dB dual-channel stero sound speaker

Expansion Slot Micro SD up to 128GB

Camera Front pixel 5 million pixels (FixedFocus)

Environmental

Operating Temperature -10°C to 50°C (14°F to 122°F)

Storage Temperature -20°C to 60°C (-4°F to 140°F)

Humidity 5% to 90% (non-condensing)

IP Rating IP54 (front only)

Wireless

WLAN RADIO IEEE 802.11 a/b/g/n/ac, 2.4GHz and 5Ghz (optional)

WPAN RADIO Bluetooth 4.0 LE, EDR + BLE (optional)

newland-id.com

Feel free to contact us or a partner near you

visit newland-id.com/partners

Specifications are subject to change without notice

© Newland EMEA 2022, all rights reserved



NQuire 750 Stingray Technical specifications

RFID	ISO/IEC 14443 A/B ISO/IEC 15693; MIFARE 1K/4K; MIFARE DESFire; Sony FeliCa (optional)
Accessories	
Optional	4G module, Magnetic card reader module, NFC reader module, RFID reader module, Desktop stand Vesa75,
	Adjustable wall mount bracket Vesa75 (all modules can be mounted on the left or right)
Software	
MDM (certified)	Ndevor, SOTI
Terminal Emulation (compatible)	StayLinked, Airwatch
Configuration Tools	Ndevor
Certifications	
Hardware	CE, RoHS, IEC/EN 62471
Warranty	
Standard	2 years



Feel free to contact us or a partner near you